

**PRODUCT-DETAILS** 

## OVR T2 1N 40-275s P QS OVR T2 1N 40-275s P QS Surge Protective Device



0	Information
General	intormation

Extended Product Type	OVR T2 1N 40-275s P QS
Product ID	2CTB815704R1400
EAN	3660308525307
Catalog Description	OVR T2 1N 40-275s P QS Surge Protective Device

Long Description

Surge protective devices SPD type 2 protect low-voltage consumer systems against surge voltages as they are tested as SPD type 2 according to IEC 61643-11. The devices are compatible with the System pro M compact series. The SPD with "TS" are optionally equipped with a auxiliary contact. The variants with "reserve varistor" (s) offer additional protection for the system, as the SPD is not completely disconnected from the mains at the end of its service life, but with an additional smaller varistor still guarantees basic protection and the system thus until the surge arrester is replaced is still protected

Technical	
Type of Low Voltage Distribution System	TT TN-S
Nominal AC Voltage of the System (U <sub>o</sub> )	230 / 400 V
Number of Protected Poles	2
Arrester Class	П
Product Main Type	T2
Standards	IEC 61643-11 / EN 61643-11

Product Type	QS
Version	Plug-in
Discharge Current	Nominal 20 kA Maximum 40 kA Total 80 kA
Impulse Current	I (imp, 10 / 350 μs) 2 kA
Maximum Continuous Operating Voltage (U <sub>c</sub> )	(L-PE) 275 V (L-L) - V (L-N) 275 V (N-PE) 275 V
Voltage Rating DC	350 V
Voltage Protection Level ( Up)	(L-N) 1.4 kV (N-PE) 1.4 kV (L-PE) 1.5 kV
Short Circuit Withstand Icc	100 kA
Temporary Overvoltage Test Value (U <sub>T</sub> )	(L-N) 337 V (N-PE) 1200 V
Short-Circuit Protective Devices	Curve B Breakers ≤ 125 A Curve C Breakers ≤ 125 A gL Type Fuses ≤ 160 A gG Type Fuses ≤ 160 A
Power Loss	28 mW
Product Name	Surge Protective Device
	To contract the construct of the transition of the contract of
Suitable For	To protect the systems against the transient overvoltage (lightning)
	To protect the systems against the transient overvoltage (lightning)
Suitable For	To protect the systems against the transient overvoltage (lightning)  35.6 mm
Suitable For Dimensions	
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height	35.6 mm 76.7 mm 88 mm
Dimensions  Product Net Width  Product Net Depth / Length	35.6 mm 76.7 mm
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings	35.6 mm 76.7 mm 88 mm 0.3 kg
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information	35.6 mm 76.7 mm 88 mm 0.3 kg 2
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information  Package Level 1 Units	35.6 mm 76.7 mm 88 mm 0.3 kg
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information	35.6 mm 76.7 mm  88 mm 0.3 kg 2
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information  Package Level 1 Units  Package Level 1 Depth /	35.6 mm 76.7 mm  88 mm 0.3 kg 2  box 1 piece 117 mm 41 mm
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information  Package Level 1 Units  Package Level 1 Depth / Length	35.6 mm 76.7 mm 88 mm 0.3 kg 2  box 1 piece 117 mm 41 mm
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information  Package Level 1 Units  Package Level 1 Depth / Length  Package Level 1 Height  Package Level 1 Height  Package Level 1 Gross	35.6 mm 76.7 mm 88 mm 0.3 kg 2
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information  Package Level 1 Units  Package Level 1 Depth / Length  Package Level 1 Height  Package Level 1 Height  Package Level 1 Gross  Weight	35.6 mm 76.7 mm  88 mm 0.3 kg 2  box 1 piece 117 mm 41 mm 41 mm  82 mm 320 g
Dimensions  Product Net Width  Product Net Depth / Length  Product Net Height  Product Net Weight  Width in Number of Modular Spacings  Container Information  Package Level 1 Units  Package Level 1 Depth / Length  Package Level 1 Height  Package Level 1 Gross  Weight  Package Level 1 EAN	35.6 mm 76.7 mm 88 mm 0.3 kg 2  box 1 piece 117 mm 41 mm 41 mm 82 mm 320 g

Certificates and Declarations (Document Number)	
CQC Certificate	9AKK107680A1974
Declaration	2CTC432056G1701
Declaration of Conformity - CE	9AKK107992A0892
Instructions and Manuals	2CTC432106M1701

Popular Downloads	
Data Sheet, Technical Information	2CTC432333D0201
Instructions and Manuals	2CTC432106M1701
Mechanical Drawings	2CTC800015F1600.pdf 2CTC800015F1601.dxf 2CTC800015F1602.stp 2CTC800015F1603.igs

Classifications	
Object Classification Code	141DCC
ETIM 4	EC000941 - Surge protection device for power supply systems
ETIM 5	EC000941 - Surge protection device for power supply systems
ETIM 6	EC000941 - Surge protection device for power supply systems
ETIM 7	EC000941 - Surge protection device for power supply systems

## Categories

 $\mbox{Low Voltage Products and Systems} \rightarrow \mbox{Modular DIN Rail Products} \rightarrow \mbox{Surge Protective Devices SPDs} \rightarrow \mbox{Surge Protective Devices SPD Class II}$ 

