

PRODUCT-DETAILS

E295-PS

E295-PS Permanent Signal Module



Canara	Information	

Extended Product Type	E295-PS
Product ID	2TAZ312005R1003
EAN	7612270939459

Catalog Description

E295-PS Permanent Signal Module

Long Description

Latching relays are electromagnetically operated devices. The E290 range from ABB can be used to realise a simple, energysaving and efficient lighting control system. These devices are mainly used in rivate houses, factory premises and commercial and public buildings as well as in industrial plants. As a rule, latching relays controlled by means of impulse buttons are installed where it is necessary for lighting to be operated from at least three different places. Each time a command is initiated (by means of an impulse button), an electrical pulse is applied to the coil of the latching relay. The coil in the device is briefly energised and activated. That short pulse to the coil leads to the mechanical latch of the internal main contacts. The internal switching mechanism enables us to achieve a safe and reliable interlock (in the same way as a ballpoint pen). Each pulse that is sent to the magnetic coil system switches the device ack to its previous position where it is held mechanically until the next control pulse is received. The devices are designed for rated currents 16 and 32A. Through the combinable accessories the main modules can be used in nearly all market applications.

Ordering

EAN	7612270939459
Minimum Order Quantity	10 piece
Customs Tariff Number	85364930

Dimensions	
Product Net Width	9 mm
Product Net Height	85 mm
Product Net Length	58 mm
Product Net Depth / Length	58 mm
Product Net Weight	41 g

Container Information		
Package Level 1 Units	box 10 piece	
Package Level 1 Width	96 mm	
Package Level 1 Height	82 mm	
Package Level 1 Depth / Length	185 mm	
Package Level 1 Gross Weight	499 g	
Package Level 1 EAN	7612270939459	

Environmental

RoHS Status Following EU Directive 2002/95/EC August 18, 2005 and amendment

^	44	: + :	:_		 	_ء			:_	-
А	dd	ıtı	Ю	na	 ın	TΟ	rm	ατ	10	n

Accessory Type	Other
Connecting Capacity	Solid 1 x 1 10 mm²
	Flexible 2 x 2.5 mm ²
	Flexible with Cable End 1 x 0.75 6 mm ²
	Flexible with Cable Lug 1 x 0.75 6 mm²
Product Main Type	E295
Product Name	Permanent Signal Module
Rated Current (I _n)	1A
Rated Frequency (f)	50 Hz
Rated Operational	250 V AC
Voltage	
RoHS Date	20170426

Certificates and Declarations (Document Number)		
Data Sheet, Technical Information	2CCC441020C0201	
Declaration of Conformity - CE	2CCC005102D0201	
Environmental Information	2CCC441012D0202	
Instructions and Manuals	2CCC441005M0801	
RoHS Information	2CCC413008D0206	

Classifications			
ETIM 4	EC000188 - Latching relay		
ETIM 5	EC000188 - Latching relay		
ETIM 6	EC002586 - Accessories for switching relay		
ETIM 7	EC002586 - Accessories for switching relay		

E295-PS 3

Object Classification K
Code

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Command\ and\ Signalling\ devices \rightarrow Latching\ Relays$

