

PRODUCT-DETAILS

AUS90

AUS90 Renovation 1,5 box



Ogólne informacje

Extended Product Type	AUS90
ID Produktu	2TKA00002897
Numer EAN	6438199004563
Opis katalogowy	AUS90 Renovation 1,5 box

Opis	The AUS90 is a front-mounted mounting box for flat socket outlet (for example 302EUJT) with telescope bottom part for board walls of 1 – 3 gypsum boards (thickness of the wall 9 – 39 mm). The height of the box is 54 – 70 mm thanks to the moving bottom part. The installation hole diameter is 73 X 90 mm (box drill AT4). At the side of the bottom part are three inlets for the 16 mm flexi pipe. There is also one inlet for the 16/20 mm and one inlet for the 20 mm flexi pipe.). There are two inlets with strain reliefs on the bottom of the box for installing 8 - 13 mm cables and two inlets for the low voltage cables. The box has four openings, one on each side, through which conductors can also be conveyed from one box to another. At the top of the box there are two fixing places for screws to install it to the log wall. At the bottom there are marking holes for drilling the installation holes overlapping each other. The protection class is IP3X. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).
------	--

Charakterystyka zamówienia

E-Number (Sweden)	1420086
Numer EAN	6438199004563
Minimalna ilość zamówienia	50 sztuka

Kod taryfy celnej

39259080

Wymiary

Szerokość produktu netto	73 mm
Wysokość produktu netto	0.055 m
Długość produktu netto	88 mm
Głębokość produktu netto	88 mm
Waga produktu netto	0.0403 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	box 50 sztuka
Szerokość opakowania (poziom 1)	0.24 m
Wysokość opakowania (poziom 1)	0.055 m
Długość opakowania (poziom 1)	0.4 m
Waga opakowania brutto (poziom 1)	2.387 kg
EAN opakowania (poziom 1)	6438199004563
Jednostka opakowania (poziom 3)	1600 sztuka
Szerokość opakowania (poziom 3)	1.2 m
Wysokość opakowania (poziom 3)	1.1 m
Długość opakowania (poziom 3)	0.8 m

Dodatkowe informacje

Średnica kabla	8...13 mm
Kolor	White
Stopień ochrony obudowy	IP3X
Konstrukcja	Device connection box (round/square)
Wewnętrzna głębokość	52 mm
Materiał	Plastic
Rodzaj montażu	Flush mounted (plaster)
Liczba biegunów	0
Typ produktu	Flush-mounted boxes
Nazwa produktu	Renovation 1,5 box
Kształt	Round
Surface Finishing	Untreated
Średnica rury	16 mm

Certyfikaty i deklaracje (Numer dokumentu)	
Arkusz danych, informacja techniczna	9AKK10103A2549
Deklaracja zgodności - CE	9AKK106713A4627
Instrukcje i podręczniki	9AKK10103A2549
Dane RoHS	9AKK106713A4634

Klasyfikacje	
ETIM 5	EC002601 - Box/housing for built-in mounting in the wall/ceiling
ETIM 6	EC002601 - Box/housing for built-in mounting in the wall/ceiling
ETIM 7	EC002601 - Box/housing for built-in mounting in the wall/ceiling
WEEE Category	Product Not in WEEE Scope

Kategorie

Produkty niskiego napięcia i systemy → Installation Materials → Flush Mounted Boxes → Plastic Installation Boxes (for WA Inserts) → Hollow Wall

