

PRODUCT-DETAILS

Sentry SSR32 24VDC

Safety Relay Sentry SSR32 24VDC - 2 NO + 2 NO (delayed) - OFF-Delay - 0.5 second



General Information	
Extended Product Type	Sentry SSR32 24VDC
Product ID	2TLA010052R0400
EAN	7350024483321
Catalog Description	Safety Relay Sentry SSR32 24VDC - 2 NO + 2 NO (delayed) - OFF-Delay - 0.5 second
Long Description	SSR32 is a safety relay with relay outputs, 2 NO + 2 delayed NO, and a +24 VDC supply voltage.
	SSR32 is used with safety devices with contacts, 1 or 2 channels , and safety devices with OSSD outputs.
	The reset function, automatic or manual, is set with a switch on the front. The two delayed NO relay outputs have an OFF-delay time of 0,5 second.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	8536419040

Popular Downloads	
Data Sheet, Technical Information	2TLC010037L0201
Instructions and Manuals	2TLC010002M0201
Dimension Diagram	2TLC010001U0201
Wiring Diagram	2TLC010011T0001
Marketing Video	2TLC010019N0201

Dimensions	
Product Net Depth / Length	120 mm
Product Net Height	120 mm
Product Net Width	22.5 mm
Product Net Weight	0.207 kg

echnical	
Performance Level (PL)	Up to e
Rated Control Supply Voltage (U _s)	24 V DC

Certificates and Declarations (Document Number)	
CCC Certificate	2020980303000244
CQC Certificate	2020980303000244
cUL Certificate	2TLC010006D0201
cULus Certificate	2TLC010007D0201
Declaration of Conformity - CCC	2020980303000244
Declaration of Conformity - CE	2TLC010010D0201
Instructions and Manuals	2TLC010002M0201
KC Certificate	2TLC010048D0201
TÜV Certificate	2TLC010008D0201

Classifications	
Object Classification Code	К
ETIM 4	EC001449 - Device for monitoring of safety-related circuits
ETIM 5	EC001449 - Device for monitoring of safety-related circuits
ETIM 6	EC001449 - Device for monitoring of safety-related circuits
ETIM 7	EC001449 - Device for monitoring of safety-related circuits
eClass	V11.0 : 27371819
UNSPSC	39122331
E-Number (Finland)	2712526
E-Number (Sweden)	3860823

Categories

Sentry SSR32 24VDC 3

