

PRODUCT-DETAILS

JSHD4H2 0,15m

JSHD4H2 3-pos device panel mounting.
6x150mm leads.



General Information

Extended Product Type	JSHD4H2 0,15m
Product ID	2TLA020002R3100
EAN	7350024455076
Catalog Description	JSHD4H2 3-pos device panel mounting. 6x150mm leads.
Long Description	Three-position device for internal panel mounting. 6x150mm leads.

Additional Information

Product Name	Three-position dual pushbutton
Function	Three-position dual pushbutton usual mounted on another device, e.g. a robot pendant
Status Indicator	No

Safety Information

Performance Level (PL)	Up to e
------------------------	---------

Technical

Communication Interface	Contacts
Connection Configuration	6 leads, 150 mm each

Number of Contacts CO	2
Number of Contacts NC	0
Number of Contacts NO	0
Rated Operational Current DC-12 (I _e)	(24 V) 0.02 A

Environmental

Degree of Protection	IP65
Ambient Air Temperature	Operation 0 ... +50 °C Storage -20 ... +80 °C
Material	Housing: PP (polypropylene with mineral filling); Rubber: Thermoplastic elastomer on PP basis; Steering T: PP with fiberglass filling

Popular Downloads

Data Sheet, Technical Information	2TLC010001C0202
-----------------------------------	-----------------

Certificates and Declarations (Document Number)

CSA Certificate	2TLC172086D0201
Declaration of Conformity - CE	2TLC172022D0201
SEMKO Certificate	2TLC172032D0201

Dimensions

Product Net Width	80 mm
Product Net Depth / Length	40 mm
Product Net Height	23 mm
Product Net Weight	0.042 kg

Ordering

Minimum Order Quantity	1 piece
Country of Origin	Sweden (SE)
Customs Tariff Number	85369095

Classifications

Object Classification Code	B
ETIM 6	EC002571 - Agreement switch
ETIM 7	EC002571 - Agreement switch
eClass	V11.0 : 27371238
UNSPSC	39122205

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices

