

PRODUCT-DETAILS

M12-3S

M12-3S M12 Y-connector



General Information

Extended Product Type	M12-3S
Product ID	2TLA020055R0600
EAN	7350024478501
Catalog Description	M12-3S M12 Y-connector
Long Description	M12-3S M12 Y-connector for series connection of DYNlink devices with the StatusBus function. One M12-5 pole female connector (#2) for connection of the safety device, one M12-5 male connector (#1) for connection of +24VDC, 0V, the incoming dynamic signal and the StatusBus and one M12-5 female connector (#3) for the outgoing inverted dynamic signal towards another safety device or Vital/Pluto safety PLC.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	8538909999

Popular Downloads

Data Sheet, Technical Information	2TLC010001C0202
Marketing Video	2TLC010019N0201 2TLC010018N0201

Dimensions

Product Net Depth / Length	20 mm
Product Net Height	40 mm
Product Net Width	35 mm
Product Net Weight	0.02 kg

Technical

Degree of Protection	IP67
Rated Control Supply Voltage (U _s)	24 V
Suitable For	Adam DYN-Status M12-5

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	No declaration needed
--------------------------------	-----------------------

Classifications

Object Classification Code	X
ETIM 4	EC002638 - Cable connector
ETIM 5	EC002638 - Cable connector
ETIM 6	EC002925 - Sensor-actuator adapting connector
ETIM 7	EC002925 - Sensor actuator adapter
eClass	V11.0 : 27060313
UNSPSC	39121438
E-Number (Sweden)	3861400

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Cables and Connectors

Low Voltage Products and Systems → Control Products → Safety Products → Safety Sensors, Switches and Locks

Low Voltage Products and Systems → Control Products → Safety Products → Safety Sensors, Switches and Locks Accessories

