

PRODUCT-DETAILS

HD5-S-104

HD5-S-104 Three-position device



Ogólne informacje

Extended Product Type	HD5-S-104
ID Produktu	2TLA023001R0200
Numer EAN	7350024485899
Opis katalogowy	HD5-S-104 Three-position device
Opis	Three-position handheld device. Potential free contacts. With 1 front and 2 top auxiliary buttons. M23-12 male connector. HD5 is suitable for Food and Beverage applications with the following features: Resistant to most chemicals, fiberglass reinforced plastic, anti-condensation membrane, IP65.

Dodatkowe informacje

Nazwa produktu	Three-position handheld device - Complete
Funkcja	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area. Developed for the Food and Beverage industry.
Funkcja dodatkowa	1 front and 2 top auxiliary buttons
Status Indicator	Tak
Zastosowanie	Suitable for Food and Beverage

Safety Information

Agencja certyfikująca	TÜV, cULus
Performance Level (PL)	Up to e
B10d Value	2 million operations to middle position 968 000 operations to bottom position

Dane techniczne

Interfejsy komunikacyjne	Contacts
Konfiguracja Podłączenia	M23-12 male
Number of Contacts CO	2
Number of Contacts NC	0
Number of Contacts NO	0
Rated Operational Current DC-12 (I_e)	(24 V) 0.02 A

Normy środowiskowe

Stopień ochrony obudowy	IP65
Material	Handle: Fiberglass reinforced plastic, PPH G30; Additional buttons: TPE; Three -position button: TF4STE_B102

Technical UL/CSA

Typ obudowy UL/CSA	1
--------------------	---

Najczęściej Pobierane

Arkusze danych, informacja techniczna	2TLC010099L0201
Instrukcje i podręczniki	2TLC010052M0201

Certyfikaty i deklaracje (Numer dokumentu)

cULus Certificate	2TLC010050D0201
Deklaracja zgodności - CE	2TLC010055D0201
Instrukcje i podręczniki	2TLC010052M0201
TÜV Certificate	2TLC010054D0201 2TLC010053D0201

Wymiary

Szerokość produktu netto	55 mm
Głębokość produktu netto	75 mm
Wysokość produktu netto	185 mm
Waga produktu netto	0.26 kg

Charakterystyka zamówienia

Minimalna ilość zamówienia	1 sztuka
Kraj pochodzenia	Niemcy (DE)
Kod taryfy celnej	85365019

Klasyfikacje

Kod klasyfikacji	X
ETIM 6	EC002571 - Agreement switch
ETIM 7	EC002571 - Agreement switch
eClass	V11.0 : 27371238
UNSPSC	39122221

Kategorie

Produkty niskiego napięcia i systemy → Aparatura sterownicza → Produkty bezpieczeństwa → Manipulatory bezpieczeństwa

