

PRODUCT-DETAILS

HD5-B-102

HD5-B-102 Three-position device AS-i



Ogólne informacje

Extended Product Type	HD5-B-102
ID Produktu	2TLA920502R0004
Numer EAN	4013614554025
Opis katalogowy	HD5-B-102 Three-position device AS-i
Opis	Three position handheld device with AS-i Integrated technology. 1 front + 2 top auxiliary buttons.Home position sensor and flashlight. M12-5 male connector. HD5 is suitable for Food and Beverage applications with the following features: Resistant to most chemicals, fiberglass reinforced plastic, anti-condensation membrane, IP65.

Dodatkowe informacje

Nazwa produktu	Three-position handheld device - Complete
Funkcja	Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area. Developed for the Food and Beverage industry.
Funkcja dodatkowa	1 front and 2 top auxiliary buttons
Funkcja dodatkowa 2	Flashlight Home position sensor
Status Indicator	Tak
Zastosowanie	Suitable for Food and Beverage

Safety Information

Agencja certyfikująca	TÜV, cULus
Performance Level (PL)	Up to e
B10d Value	2 million operations to middle position 968 000 operations to bottom position

Dane techniczne

Interfejsy komunikacyjne	AS-i
Konfiguracja Podłączenia	M12-5 male
Number of Contacts CO	2
Number of Contacts NC	0
Number of Contacts NO	0
Rated Operational Current DC-12 (I_{e1})	(24 V) 0.02 A

Normy środowiskowe

Stopień ochrony obudowy	IP65
-------------------------	------

Technical UL/CSA

Typ obudowy UL/CSA	1
--------------------	---

Najczęściej Pobierane

Arkusz danych, informacja techniczna	2TLC010093L0201
Instrukcje i podręczniki	2CDC172107D0201
Dimension Diagram	2CDC172112D0201

Certyfikaty i deklaracje (Numer dokumentu)

cULus Certificate	2TLC010050D0201
Deklaracja zgodności - CE	2TLC010045D0201
Instrukcje i podręczniki	2CDC172107D0201
TÜV Certificate	2TLC010054D0201 2TLC010053D0201

Wymiary

Szerokość produktu netto	55 mm
Głębokość produktu netto	75 mm
Wysokość produktu netto	185 mm
Waga produktu netto	0.26 kg

Charakterystyka zamówienia	
Minimalna ilość zamówienia	1 sztuka
Kraj pochodzenia	Niemcy (DE)
Kod taryfy celnej	85365019

Klasyfikacje	
Kod klasyfikacji	X
ETIM 6	EC002571 - Agreement switch
ETIM 7	EC002571 - Agreement switch
eClass	V11.0 : 27371238
UNSPSC	39122221

Kategorie
Produkty niskiego napięcia i systemy → Aparatura sterownicza → Produkty bezpieczeństwa → Manipulatory bezpieczeństwa

