
## Quarter turn actuator DSRL-16-180-P-FW Part number: 30655

**FESTO** 





General operating condition

## **Data sheet**

| Feature                          | Value   |
|----------------------------------|---|
| Size                             | 16  |
| Cushioning angle                 | 2.1 deg                                       |
| Adjustment range of swivel angle | 0 deg 180 deg                                 |
| Swivel angle                     | 0 deg 180 deg                                 |
| Cushioning                       | Elastic cushioning rings/pads at both ends    |
| Mounting position                | Any   |
| Mode of operation                | Double-acting Double-acting                   |
| Structural design                | Rotary vane                                   |
| Position sensing                 | None  |
| Symbol                           | 00991265                                      |
| Operating pressure               | 2 bar 8 bar                                   |
| Max. swivel frequency at 6 bar   | 3 Hz  |
| Operating medium                 | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| LABS (PWIS) conformity           | VDMA24364-B2-L                                |
| Ambient temperature              | -10 °C 60 °C                                  |
| Max. axial force                 | 30 N  |
| Max. radial force                | 75 N  |
| Theoretical torque at 6 bar      | 2 Nm  |
| Product weight                   | 300 g   |
| Type of mounting                 | With through-hole                             |
| Pneumatic connection             | M5  |
| Covering material                | PA-reinforced                                 |
| Drive shaft material             | Steel<br>Nickel-plated                        |
| Seals material                   | NBR   |
| Housing material                 | Die-cast zinc                                 |