



Main

Range	Compact
Product or component type	Switch disconnecter
Product name	Compact INS
Poles description	3P
Network type	DC AC
Network frequency	50/60 Hz
[Ie] rated operational current	AC-22A: 200 A AC 50/60 Hz 220/240 V AC-22A: 200 A AC 50/60 Hz 380/415 V AC-22A: 200 A AC 50/60 Hz 440/480 V AC-22A: 200 A AC 50/60 Hz 480 V NEMA AC-22A: 200 A AC 50/60 Hz 500/525 V AC-22A: 200 A AC 50/60 Hz 660/690 V AC-23A: 200 A AC 50/60 Hz 220/240 V AC-23A: 200 A AC 50/60 Hz 380/415 V AC-23A: 200 A AC 50/60 Hz 440/480 V AC-23A: 200 A AC 50/60 Hz 480 V NEMA AC-23A: 200 A AC 50/60 Hz 500/525 V AC-23A: 200 A AC 50/60 Hz 660/690 V DC-22A: 200 A DC 125 V 2 poles in series DC-23A: 200 A DC 125 V 2 poles in series
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Ith] conventional free air thermal current	200 A at 60 °C
[Icm] rated short-circuit making capacity	30 kA switch-disconnector alone 690 V AC at 50/60 Hz 330 kA with upstream protection circuit breaker 690 V AC at 50/60 Hz
[Ue] rated operational voltage	125 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Pollution degree	3
------------------	---

## Complementary

Control type	Direct front rotary handle
Handle colour	Black
Mounting mode	Fixed
Mounting support	Plate Rail
Upside connection	Front
Downside connection	Front
Maximum power	AC-23: 110 kW at 440 V AC 50/60 Hz AC-23: 110 kW at 480 V AC 50/60 Hz (NEMA) AC-23: 132 kW at 500/525 V AC 50/60 Hz AC-23: 160 kW at 660/690 V AC 50/60 Hz AC-23: 55 kW at 220/240 V AC 50/60 Hz AC-23: 55 kW at 230 V AC 50/60 Hz (NEMA) AC-23: 90 kW at 380/415 V AC 50/60 Hz
Rated duty	Uninterrupted
[I <sub>cw</sub> ] rated short-time withstand current	1.8 kA during 30 s conforming to IEC 60947-3 2.2 kA during 20 s conforming to IEC 60947-3 4.9 kA during 3 s conforming to IEC 60947-3 8.5 kA during 1 s conforming to IEC 60947-3
Mechanical durability	15000 cycles
Electrical durability	AC-22A: 1500 cycles 440 V AC 50/60 Hz AC-22A: 1500 cycles 500 V AC 50/60 Hz AC-22A: 1500 cycles 690 V AC 50/60 Hz AC-23A: 1500 cycles 440 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 690 V AC 50/60 Hz DC-22A: 1500 cycles 125 V DC 2 poles in series DC-23A: 1500 cycles 125 V DC 2 poles in series
Connection pitch	35 mm
Height	136 mm
Width	140 mm
Depth	96 mm
Product weight	2 kg

## Environment

Standards	IEC 60947-1 IEC 60947-3
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
------	---

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---