

# Clevis foot LBG-63

Part number: 31764

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                            | Value                                                                                                                                                                                                                                                                 |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 63                                                                                                                                                                                                                                                                    |
| Corrosion resistance class (CRC)                   | 2 - Moderate corrosion stress                                                                                                                                                                                                                                         |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                                                                        |
| Suitability for the production of Li-ion batteries | Metals with more than 1% by mass of copper are excluded from use.<br>Circuit boards, Lines, electrical push-in connectors and Coils Metals with more than 1% copper as an alloy component are excluded from use.<br>Exceptions are printed circuit boards, cables, el |
| Ambient temperature                                | -40 °C ... 150 °C                                                                                                                                                                                                                                                     |
| Max. load capacity                                 | 4 kN                                                                                                                                                                                                                                                                  |
| Product weight                                     | 580 g                                                                                                                                                                                                                                                                 |
| Product weight                                     | 20.44 oz                                                                                                                                                                                                                                                              |
| Note on materials                                  | RoHS-compliant                                                                                                                                                                                                                                                        |
| Mounting material                                  | Cast stainless steel                                                                                                                                                                                                                                                  |
| Bolt material                                      | Case-hardened steel                                                                                                                                                                                                                                                   |
| Fuse material                                      | Spring steel                                                                                                                                                                                                                                                          |