

# Barb tubing fitting N-3/8-P-9

Part number: 3609

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                         | Value                                                              |
|-------------------------------------------------|--------------------------------------------------------------------|
| Nominal width                                   | 7.6 mm                                                             |
| Type of seal on screwed plug                    | Sealing ring                                                       |
| Mounting position                               | Any                                                                |
| Design                                          | Straight design                                                    |
| Pack size                                       | 1                                                                  |
| Operating pressure for entire temperature range | -0.95 bar ... 16 bar                                               |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-]                      |
| Information on operating and pilot media        | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)                | 2 - Moderate corrosion stress                                      |
| LABS (PWIS) conformity                          | VDMA24364-B1/B2-L                                                  |
| Ambient temperature                             | -10 °C ... 60 °C                                                   |
| Max. tightening torque                          | 15 Nm                                                              |
| Product weight                                  | 8.77 g                                                             |
| Pneumatic connection 1                          | External thread G3/8                                               |
| Pneumatic connection 2                          | for pneumatic tubing inside diameter 9 mm                          |
| Note on materials                               | RoHS-compliant                                                     |
| Housing material                                | Aluminum, anodized                                                 |