

SWITCH-DISCONNECTOR 400A, FRAME SIZE 3, 3-
POLE FRONT OPERATING LEFT BASIC UNIT
WITHOUT HANDLE FLAT TERMINAL

Model		
product brandname		SENTRON
Product designation		Switching device
Design of the product		3KD switch disconnectors
Display version / for switch position indicator door-coupling rotary operating mechanism		ON-OFF
Design of the operating mechanism		without
Design of handle		without
Type of the driving mechanism / motor drive		No

General technical data		
Number of poles		3
Type of device		fixed mounting
Size of switch disconnector		3
Electrical endurance (switching cycles)		
• at AC-23 A / at 690 V / at 50/60 Hz		1 000
• at DC-23 A / at 440 V		1 000
• I2t value / with closed switch / for combination switch + fuse / at 500 V / maximum	A²·s	1 165 000
• I2t value / with closed switch / for combination switch + fuse / at 400 V / maximum	A²·s	1 165 000
• I2t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum	A²·s	1 157 500
• I2t value / with closed switch / at 690 V / for combination switch + aM fuse / maximum	A²·s	1 267 900
• I2t value / of the fuse / at 500 V / maximum permissible	A²·s	2 150 005
• I2t value / of the gG fuse / at 690 V / maximum permissible	A²·s	1 650 005
circuit-breaker / Design		3KD4
Mechanical service life (switching cycles) / typical		10 000
Position / of the switch operating mechanism		at the left end
Overvoltage category		IV

Voltage		
Operating voltage / with current paths in series		

• with degree of pollution 2 / at DC / rated value / Note		440 / 3
• with degree of pollution 3 / at DC / rated value / Note		440 / 3
Insulation voltage		
• rated value	V	1 000
Surge voltage resistance / rated value	kV	12
Overvoltage in percent / relative to the operating voltage / at AC / at 50/60 Hz	%	10

Protection class		
Protection class IP		IP00
Protection class IP		
• with closed switch / with cover or cable lug cover		IP20
• on the front		IP00

Dissipation		
Power loss [W]		
• with conventional rated thermal current / per pole	W	17

Electricity		
• Operating current / at AC-21 A / at 400 V / maximum	A	400
• Operating current / at AC-21 A / at 500 V / maximum	A	400
• Operating current / at AC-21 A / at 690 V / maximum	A	400
• Operating current / at AC-23 A / at 500 V / at 50/60 Hz / rated value / maximum	A	350
• Operating current / at AC-22 A / at 500 V / at 50/60 Hz / rated value / maximum	A	400
• Operating current / at AC-22 A / at 400 V / at 50/60 Hz / rated value / maximum	A	400
• Operating current / at AC-22 A / at 690 V / at 50/60 Hz / rated value / maximum	A	400
• Operating current / at AC-23 A / at 400 V / at 50/60 Hz / rated value / maximum	A	400
• Operating current / at AC-23 A / at 690 V / at 50/60 Hz / rated value / maximum	A	315
• Operating current / at DC-23 A / at 440 V / rated value / maximum		400 / 3
• Operating current / at DC-23 A / at 220 V / rated value / maximum		400 / 2

- Operating current / at DC-22 A / at 440 V / rated value / maximum - Operating current / at DC-22 A / at 220 V / rated value / maximum - Operating current / at DC-21 A / at 440 V / rated value / maximum - Operating current / at DC-21 A / at 220 V / maximum / Note		400 / 3 400 / 2 400 / 3 400 / 2
Continuous current		
- rated value - at 40 °C / rated value - at 45 °C / rated value - at 50 °C / rated value - at 55 °C / rated value - at 60 °C / rated value - at 65 °C / rated value - at 70 °C / rated value	A A A A A A A A	400 400 400 400 400 400 400 400
Continuous current / at DC / rated value	A	400
Let-through current / of the fuse / at 500 V / maximum permissible	A	34 348
Let-through current / of the gG fuse / at 690 V / maximum permissible	A	33 005
Let-through current / with closed switch		
- at 690 V / for combination switch + aM fuse / maximum permissible - at 690 V / for combination switch + gG fuse / maximum permissible - for combination switch + fuse / at 400 V / maximum permissible - for combination switch + fuse / at 500 V / maximum permissible	A A A A	27 300 27 960 35 200 35 200
Short-time current resistance (Icw)		
- limited to 1 s / rated value - at 690 V AC/440 V DC / limited to 1 s / rated value	kA kA	13 13
Main circuit		
Operating power		
- at AC-23 A / at 400 V / at 50/60 Hz / rated value - at AC-23 A / at 500 V / at 50/60 Hz / rated value - at AC-23 A / at 690 V / at 50/60 Hz / rated value	kW kW kW	220 250 315
Operating voltage		
at AC / at 50/60 Hz / rated value	V	690
Auxiliary circuit		

Number of connected NC contacts / for auxiliary contacts		0
Number of connected NO contacts / for auxiliary contacts		0
Number of connected CO contacts / for auxiliary contacts		0
Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		6
Number of NO contacts / for auxiliary contacts		6

Suitability

Suitability for use		
• Main switch		Yes
• switch disconnecter		Yes
• EMERGENCY OFF switch		No
• safety switch		Yes
• maintenance/repair switch		Yes

Product details

Product feature / interlock		No
Product component		
• Trip indicator		No
• Voltage trigger		No
• undervoltage release		No
• undervoltage release with leading contact		No
Product extension		
• Auxiliary switch		Yes
• optional		
— motor drive		No
— Voltage trigger		No

Short circuit

• Short-circuit current making capacity (I _{cm}) / for switch disconnecter / at 690 V AC/440 V DC / without fuse link / rated value / minimum	kA	26
• Short-circuit current making capacity (I _{cm}) / for switch disconnecter / without fuse link / rated value / minimum	kA	26
Conditional short-circuit current		
• with line-side fuse protection / at 500 V / by gG fuse / rated value	kA	65

Connections

• Type of connectable conductor cross-sections / for copper busbar		1x (30x10mm ²)
--	--	----------------------------

- Type of connectable conductor cross-sections / for aluminum conductor / stranded / with lug - Type of connectable conductor cross-sections / for copper conductor / stranded / with lug / acc. to DIN 46234 - Type of connectable conductor cross-sections / for copper conductor / stranded / with lug / acc. to DIN 46235	1x (25 ... 240mm ²), 2x (25 ... 120mm ²) 1x (6 ... 240mm ²), 2x (6 ... 150mm ²) 1x (16 ... 185mm ²), 2x (16 ... 150mm ²)
Type of electrical connection for main current circuit	flat connector

Mechanical Design		
Height	mm	164
Width	mm	190
Depth	mm	93.5
Mounting position		any
Mounting type		floor mounting
Mounting type		
- front mounting with 4-hole attachment - front mounting with central attachment - rail mounting		No No No
Net weight	g	2 800

Environmental conditions		
Degree of pollution		3
Ambient temperature		
- during operation / minimum - during operation / maximum - during storage / minimum - during storage / maximum	°C °C °C °C	-25 70 -50 80

Certificates		
Equipment marking		
- acc. to DIN EN 61346-2 - acc. to DIN EN 81346-2		Q Q

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



[sonstig](#)



Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3KD4230-0PE10-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3KD4230-0PE10-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KD4230-0PE10-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

10/14/2016