

SECTION FUS-NH 4x 63A SANS COMM

Model	
product designation	switch disconnecter with fuses
design of the product	for NH C00
fuse system	NH C00
Supply voltage	
operating voltage at DC rated value	220 V
Protection class	
protection class IP	IP00
Main circuit	
operational current rated value	63 A
suitability for use safety switch	Yes
Connections	
type of electrical connection for main current circuit	BUSBAR CONNECTION
Mechanical Design	
height	105 mm
width	142 mm
depth	86.5 mm
fastening method	Surface mounting and installation
net weight	1.1 kg
Environmental conditions	
ambient temperature during operation	
• minimum	-20 °C
• maximum	45 °C
ambient temperature during storage minimum	-25 °C
Approvals Certificates	
General Product Approval	Test Certificates



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

other	Environment
Confirmation	Miscellaneous
	Environmental Confirmations
	Environmental Confirmations

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7113-4AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7113-4AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7113-4AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

last modified:

5/26/2025 

