

SWITCH DISCONNECTOR WITH FUSES

Model		
version		for NH C00
Design type		Basic version without handle
Dissipation		
Power loss [W]		
• maximum	W	142
Main circuit		
Operating voltage		
• rated value	V	690
• at AC / at 50/60 Hz / rated value	V	690
• at DC / rated value	V	220
Connections		
Type of connection, main circuit		busbar terminal
Mechanical Design		
Height	m	105
Width	m	142
Depth	m	86.5
Type of mounting		fixed mounted
Mounting type		Surface mounting and installation
Environmental conditions		
Ambient temperature		
• during operation / minimum	°C	-20
• during operation / maximum	°C	45
Certificates		
Equipment marking / acc. to DIN EN 61346-2		Q
Declaration of Conformity	other	



[Umweltbestätigung](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3KL7114-4AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3KL7114-4AA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7114-4AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>