

SECTION FUS-NH 3x 100 A SANS COMM

Model	
product designation	switch disconnecter with fuses
design of the product	for NH 00
fuse system	NH 00
Supply voltage	
operating voltage / at DC / rated value	220 V
Protection class	
protection class IP	IP00
Main circuit	
operational current / rated value	100 A
suitability for use	
• safety switch	Yes
Connections	
type of electrical connection / for main current circuit	BUSBAR CONNECTION
Mechanical Design	
height	147 mm
width	168 mm
depth	94.5 mm
fastening method	Surface mounting and installation
net weight	1.9 kg
Environmental conditions	
ambient temperature / during operation	
• minimum	-20 °C
• maximum	45 °C
ambient temperature / during storage / minimum	-25 °C
General Product Approval	
	other

[Confirmation](#)



[Environmental Con-
firmations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7121-3DA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7121-3DA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7121-3DA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



