

SECTION FUS-NH 4x 200 A SANS COMM

Model		
product designation	switch disconnecter with fuses	
design of the product	for NH 1	
fuse system	NH 1	
Supply voltage		
operating voltage at DC rated value	220 V	
Protection class		
protection class IP	IP00	
Main circuit		
operational current rated value	200 A	
suitability for use		
• safety switch	Yes	
Connections		
type of electrical connection for main current circuit	BUSBAR CONNECTION	
Mechanical Design		
height	196 m	
width	235 m	
depth	113 m	
fastening method	Surface mounting and installation	
net weight	5.3 kg	
Environmental conditions		
ambient temperature during operation		
• minimum	-20 °C	
• maximum	45 °C	
ambient temperature during storage minimum	-25 °C	
Approvals Certificates		
General Product Approval	EMV	Test Certificates



EG-Konf.



[Miscellaneous](#)



[Type Test Certificates/Test Report](#)

Marine / Shipping

other

Environment



LRS

[Confirmation](#)

[Miscellaneous](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3KL7131-4AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7131-4AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7131-4AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

last modified:

9/14/2021 

