

### SWITCH DISCONNECTOR WITH FUSES

| Model                                      |       |                                   |
|--------------------------------------------|-------|-----------------------------------|
| version                                    |       | for NH 1                          |
| Design type                                |       | Basic version without handle      |
| Dissipation                                |       |                                   |
| Power loss [W]                             |       |                                   |
| • maximum                                  | W     | 235                               |
| Main circuit                               |       |                                   |
| Operating voltage                          |       |                                   |
| • rated value                              | V     | 690                               |
| • at AC / at 50/60 Hz / rated value        | V     | 690                               |
| • at DC / rated value                      | V     | 220                               |
| Connections                                |       |                                   |
| Type of connection, main circuit           |       | busbar terminal                   |
| Mechanical Design                          |       |                                   |
| Height                                     | m     | 196                               |
| Width                                      | m     | 235                               |
| Depth                                      | m     | 113                               |
| Type of mounting                           |       | fixed mounted                     |
| Mounting type                              |       | Surface mounting and installation |
| Environmental conditions                   |       |                                   |
| Ambient temperature                        |       |                                   |
| • during operation / minimum               | °C    | -20                               |
| • during operation / maximum               | °C    | 45                                |
| Certificates                               |       |                                   |
| Equipment marking / acc. to DIN EN 61346-2 |       | Q                                 |
| Declaration of Conformity                  | other |                                   |



[Umweltbestätigung](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3KL7132-4AA00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3KL7132-4AA00/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3KL7132-4AA00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3KL7132-4AA00)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>