

SITOR cylindrical fuse link, 10 x 38 mm, 10 A, gR, Un AC: 690 V, Un DC: 440 V



Figure similar

Model	
Product designation	SITOR cylindrical fuse link
General technical data	
Operating class of the fuse link	gR
Size of the fuse link	10x38 mm
Supply voltage / at DC	440 V
Main circuit	
Operating voltage / rated value	690 V
Operating current / Rated value	10 A
Product details	
Product component / striker	No
Mounting position	Any, preferably vertical
Net weight	10 g
Reference identifier	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F



UR

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NC1010-0MK>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NC1010-0MK>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC1010-0MK

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

