

SITOR FUSE-LINK SIZE 3 690V,1000A WITH INT. THREAD M12



Similar to image

**Technical data:**

<b>Current / for AC / rated value</b>	A	1,000
<b>Size of the fallback-system / acc. to DIN EN 60269-1</b>		NH2
<b>Supply voltage</b>		
• for AC / rated value	V	690
• for DC	V	440
<b>Switching capacity current</b>		
• in accordance with IEC 60947-2 / rated value	kA	100
<b>Design of an identification indicator</b>		without
<b>Ambient temperature</b>	°C	-20 ... +50
<b>Varying load factor (WL)</b>		0.85

**Certificates/approvals:**

General Product Approval

Declaration of Conformity



**Further information:**

---

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

---

**Industry Mall (Online ordering system)**

<http://www.siemens.com/lowvoltage/mall>

---

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/3NC3241-6B/all>

---

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NC3241-6B](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC3241-6B)

---

**CAX-Online-Generator**

<http://www.siemens.com/cax>

---

**last change:**

Feb 15, 2013