

SITOR fuse link, with female thread on both sides, NH3,
In: 1000 A, aR, Un AC: 1000 V, Un DC: 440 V, Front
indicator

Model		
product brand name		SETRON
Design of an identification indicator		front indicator
Design of the fuse link		SITOR, LV HRC design
General technical data		
Size of fuse system / acc. to DIN EN 60269-1		NH3
Operating class of the fuse link		aR
circuit-breaker / Design		3NC
Varying load factor (WL)		0.95
Supply voltage / at DC	V	440
Switching capacity		
Switching capacity current		
• acc. to IEC 60947-2 / rated value	kA	100
Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	165
• maximum	W	165
Electricity		
rated current In / IEC, DIN/VDE / at 40 Cel	A	950
Current / at AC / rated value	A	1 000
Mechanical Design		
Mounting position		Any, preferably vertical
Net weight	g	1 006
Environmental conditions		
Ambient temperature		
• minimum	°C	-20
• maximum	°C	50
Environmental category		-20 to +50 at 95% relative humidity
Certificates		
Equipment marking		
• acc. to DIN EN 61346-2		F

General Product Approval

Declaration of Conformity



CCC



UR



sonstig



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NC3341-6U>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NC3341-6U/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NC3341-6U

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

08/11/2016