



LV HRC FUSE LINK A.M. W. NON-INSULATED GRIPPING LUGS SIZE 2, 200A, AC 690 V

Similar to image

Technical data:		
Current / for AC / rated value	A	200
Size of the fallback-system / acc. to DIN EN 60269-1		NH2
Supply voltage		
• for AC / rated value	V	690
• for DC	V	250
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	120
Design of an identification indicator		Front indicators
Protection class IP		IP20, with connected conductors
Climatic class		-20 to +50 at 95% relative humidity
Ambient temperature		
• minimum	°C	-20
• maximum	°C	50

Certificates/approvals:

General Product Approval	Declaration of Conformity	Test Certificates	
 GOST	 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<http://support.automation.siemens.com/WW/view/en/3ND2240/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3ND2240

CAX-Online-Generator

<http://www.siemens.com/cax>



last change:

Jan 28, 2013