

SITOR fuse link, with slotted blade contacts, NH2, In:
125 A, aR, Un AC: 1000 V, Front indicator



Figure similar

Model		
product brand name		SETRON
Design of an identification indicator		front indicator
Design of the fuse link		SITOR, LV HRC design
General technical data		
Size of fuse system / acc. to DIN EN 60269-1		NH2
Operating class of the fuse link		aR
circuit-breaker / Design		3NE
Varying load factor (WL)		1
Switching capacity		
Switching capacity current		
• acc. to IEC 60947-2 / rated value	kA	100
Electricity		
rated current In / IEC, DIN/VDE / at 40 Cel	A	125
Current / at AC / rated value	A	125
Mechanical Design		

Mounting position		Any, preferably vertical
-------------------	--	--------------------------

Environmental conditions

Ambient temperature		
	• minimum	°C -20
	• maximum	°C 50
Environmental category		-20 to +50 at 95% relative humidity

Certificates

Equipment marking		
	• acc. to DIN EN 61346-2	F
	• acc. to DIN EN 81346-2	F

General Product Approval	Declaration of Conformity	other
--------------------------	---------------------------	-------



[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NE3322>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NE3322/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE3322

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

08/11/2016