



SITOR FUSE-LINK FOR SEMICONDUCTOR PROTECTION
355A GR 1000V SIZE 3 CONNECTION CONTACT
INDICATOR 130MM

Similar to image

Technical data:

product brand name		SETRON
Current / for AC / rated value	A	355
Operating class of the fuse link		gR
Size of the fallback-system / acc. to DIN EN 60269-1		NH3
Supply voltage		
• for AC / rated value	V	1,000
• for DC	V	440
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	100
Design of an identification indicator		others
mounting position		Any, preferably vertical
Climatic class		-20 to +50 at 95% relative humidity
Ambient temperature	°C	-20 ... +50
Design of the switching contact		Non-corroding, silver-plated
Reference code / according to DIN EN 61346-2		F
Item designation / according to DIN EN 81346-2		F

Certificates/approvals:

**General Product
Approval**

Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NE3434-3C>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NE3434-3C/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE3434-3C

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jul 14, 2014