

SITOR fuse link, with slotted blade contacts, NH2, In: 450 A, aR, Un
AC: 750 V, Front indicator



Figure similar

Model	
product brandname	SETRON
Design of an identification indicator	front indicator
Design of the fuse link	SITOR, LV HRC design
General technical data	
Size of fuse system / acc. to DIN EN 60269-1	NH2
Operating class of the fuse link	aR
circuit-breaker / Design	3NE
Varying load factor (WL)	0.9
Switching capacity	
Switching capacity current	100 kA
• acc. to IEC 60947-2 / rated value	
Dissipation	
Power loss [W]	70 W
• for rated value of the current / at AC / in hot operating state / per pole	

Electricity

rated current I _n / IEC, DIN/VDE / at 40 Cel	450 A
Current / at AC / rated value	450 A

Mechanical Design

Mounting position	Any, preferably vertical
Net weight	770 g

Environmental conditions

Ambient temperature	
• minimum	-20 °C
• maximum	50 °C
Environmental category	-20 to +50 at 95% relative humidity

Certificates

Equipment marking	
• acc. to DIN EN 61346-2	F
• acc. to DIN EN 81346-2	F

General Product Approval



CCC

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NE4333-3>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NE4333-3/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NE4333-3

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

