



FEED-IN BLOCK I=1000A, U=690V,
3-POLE SWITCHABLE TRIPLE-POLE SWITCHABLE NEW
DESIGN

Similar to image

General technical details:		
Continuous current / rated value	A	1,000
Operating voltage at 50/60 Hz / for AC / rated value	V	690
Number of poles		3
Active power loss / maximum	W	300
Item designation according to DIN EN 61346-2		Q

Mechanical design:		
Design of the load switch Strip form		Yes
Type of mounting		Flachanschluss, 2 x M 12
Design of the electrical connection for main current circuit		flat connector
Fuse system		LV HRC fuse
Center line spacing 40 mm 50 mm 60 mm	mm	185 No No No

- 100 mm
- 185 mm

	No
	Yes

Ambient conditions:

Ambient temperature

- during operating

°C

-25 ... +55

Depth

mm

248

Height

mm

762

Width

mm

99.5

Certificates/approvals:

General Product Approval

Test Certificates

other



[Special Test Certificate](#)

[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NJ4153-5BD01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ4153-5BD01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Dec 3, 2012