



FUSE-SWITCH-DISCONNECTOR 3-POLE SWITCHABLE,
NEW DESIGN FOR SECONDARY-SIDE PROTECTION OF
TRANSFORMERS UP TO 630 KVA FOR LV HRC
FUSES GTR 910 A MAX.,
400V AC,
AND NH3 DISCONN.PLATE UP TO 1250 A.

Similar to image

General technical details:

Continuous current / rated value	A	910
Operating voltage • at 50/60 Hz / for AC / rated value	V	690
Number of poles		3
Active power loss / maximum	W	260
Item designation • according to DIN EN 61346-2		Q

Mechanical design:

Design of the load switch • Strip form		Yes
Type of mounting		Flachanschluss, 2 x M 12
Design of the electrical connection • for main current circuit		flat connector
Fuse system		LV HRC fuse
Center line spacing • 40 mm • 50 mm • 60 mm	mm	185 No No No

- 100 mm
- 185 mm

	No
	Yes

Ambient conditions:

Ambient temperature

- during operating

°C

-25 ... +55

Depth

mm

195

Height

mm

662

Width

mm

99.5

Certificates/approvals:

General Product Approval

Test Certificates

other



[Special Test Certificate](#)

[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NJ4183-3BF01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ4183-3BF01

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Dec 3, 2012