



IN-LINE FUSE SWITCH DISCONNECTOR 1-POLE
SWITCHABLE,
SIZE 4A,
I=1250A FLAT-TYPE TERMINAL M16 X 60

Similar to image

General technical details:

Continuous current / rated value	A	1,250
Operating voltage		
• for DC / rated value	V	440
• at 50/60 Hz / for AC / rated value	V	690
Number of poles		3
Active power loss / maximum	W	300
Item designation		
• according to DIN EN 61346-2		Q

Mechanical design:

Design of the load switch		
• Strip form		Yes
Type of mounting		Stehbolzenanschluss, M16 x 60 mm
Design of the electrical connection		
• for main current circuit		flat connector
Fuse system		LV HRC fuse
Center line spacing	mm	185
• 40 mm		No
• 50 mm		No

- 60 mm
- 100 mm
- 185 mm

No
No
Yes

Ambient conditions:

Ambient temperature

- during operating

°C

-25 ... +55

Depth

mm

240.5

Height

mm

775

Width

mm

248

Certificates/approvals:

General Product Approval

other



[Declaration of Conformity](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NJ5643-0BB00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ5643-0BB00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Dec 3, 2012