

ACCESSORY FOR DISCONNECTOR-FUSE IN-LINE TYPE,  
CAN BE PLUGGED IN GUIDE RAILS DEPTH 200MM



Similar to image

### Technical data:

|                                 |  |                     |
|---------------------------------|--|---------------------|
| Design type                     |  | -                   |
| Type, explanations              |  | -                   |
| Type, explanations additionally |  | -                   |
| Accessories                     |  | Withdrawable device |

### Certificates/approvals:

|                          |     |
|--------------------------|-----|
| General Product Approval | EMC |
|--------------------------|-----|



### Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NJ6900-4FB00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3NJ6900-4FB00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NJ6900-4FB00)

**last change:**

Feb 14, 2013