



SENTRON, fuse switch disconnecter 3NP1, 1-pole, NH1, 250 A, for assembly and installation on mounting plate, Flat terminal, cover level 70mm

Model	
product brand name	SENTRON
product designation	3NP1 fuse switch disconnecter
design of the product	cover level 70 mm
design of the safety monitoring	Without
design of the actuating element	Cover handle
design of the load switch / strip form	No
type of the driving mechanism / motor drive	No
General technical data	
number of poles	1
type of device	For assembly and installation on mounting plate
size of disconnecting link	1 and 0
size of fuse link	NH0, NH1
let-through current / with closed switch / maximum permissible	32 kA
mechanical service life (switching cycles) / typical	1 600
power factor	
• at AC-22 B	0.65
• at AC-23 B	0.35
• with capacitive load	-0.25
fuse system	LV HRC fuse
degree of pollution	3
Voltage	
insulation voltage	
• rated value	690 V
• with degree of pollution 3 / at AC / rated value	690 V
• with degree of pollution 2 / at AC / rated value	1 000 V
power factor / at AC-21 B	0.95
surge voltage resistance / rated value	8 kV
operating voltage	
• at AC / rated value / maximum	240 V
• at DC / rated value	120 V
• at DC / rated value / maximum	120 V
Protection class	
protection class IP	
• with closed switch / with cover or cable lug cover	IP40
• with closed switch / without cover or cable lug cover	IP30
• on the front	IP40
• open	IP20

Dissipation

power loss [W]	
• with conventional rated thermal current / without fuse / per pole	8 W
• with conventional rated thermal current / without fuse / per device	8 W
• for rated value of the current / at AC / in hot operating state / per pole	31 W
• of the fuse / per fuse / maximum	23 W

Current

operational current	
• at 35 °C / rated value	250 A
• at 40 °C / rated value	245 A
• at 45 °C / rated value	240 A
• at 50 °C / rated value	233 A
• at 55 °C / rated value	233 A
• at AC / rated value	250 A
• at AC-23 B / at 240 V / rated value	250 A
• at AC-22 B / at 240 V / rated value	250 A
• at AC-21 B / at 240 V / rated value	250 A
• at DC-23 B / at 120 V / rated value	200 A
• at DC-22 B / at 120 V / rated value	250 A
• at DC-21 B / at 120 V / rated value	250 A
let-through current / with high-speed activation / maximum permissible	25 kA

Main circuit

operational current	
• rated value	250 A
• with capacitive load / at 400 V / rated value	72 A
• with capacitive load / at 500 V / rated value	55 A

Auxiliary circuit

number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0

Suitability

suitability for use	
• main switch	No
• switch disconnecter	Yes
• EMERGENCY OFF switch	No
• safety switch	Yes
• maintenance/repair switch	Yes

Product details

product feature / interlock	Yes
• product component / trip indicator	No
• product function / phase failure monitoring	No
• product component / undervoltage release	No
• product component / undervoltage release with leading contact	No
product feature / sealable	Yes
product extension / auxiliary switch	Yes
product extension / optional	
• locking capability	Yes
• motor drive	No
• phase failure monitoring	No
• fuse monitoring	Yes
• voltage trigger	No
• overvoltage protection monitoring	No

Product function

product function	
• fuse monitoring	No

• overvoltage protection monitoring	No
Connections	
arrangement of electrical connectors / for main current circuit	other
connectable conductor cross-section / for main contacts	
• solid or stranded / minimum	16 mm ²
• solid or stranded / maximum	150 mm ²
• stranded / minimum	16 mm ²
• stranded / maximum	150 mm ²
tightening torque / with screw-type terminals	
• minimum	10 N·m
• maximum	12 N·m
type of connectable conductor cross-sections / of the laminated conductors / maximum	25 x 18 mm
type of connection technology	Flat terminal
type of electrical connection / for main current circuit	busbar connection

Mechanical Design	
height	306 mm
width	69.7 mm
depth	116 mm
fastening method	mounting plate
fastening method	
• floor mounting	Yes
• 4-hole front mounting	No
• front mounting with central attachment	No
• rail mounting	No
mounting position	horizontal/vertical

Environmental conditions	
ambient temperature / during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature / during storage	
• minimum	-50 °C
• maximum	80 °C

General Product Approval	Declaration of Conformity	Test Certificates
---------------------------------	----------------------------------	--------------------------

[Miscellaneous](#)



[UK Declaration of Conformity](#)



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Marine / Shipping	other
--------------------------	--------------



[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3NP1141-1DA10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3NP1141-1DA10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP1141-1DA10

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications





