



FUSE-SWITCH-DISCONNECTOR 3-POLE, NH1, 250A 60MM BUSBAR SYSTEM COVERS FOR RITTAL FLAT CONNECTOR FUSE MONITORING ELECTRONIC, EFM 20

Similar to image

General technical details:

Number of poles	3
product brand name	SENTRON
Product designation	Fuse switch disconnecter
Fuse system	LV HRC fuse
Installation size of fuse-link	NH0, NH1
Installation size of disconnecting link	1 and 0
Type from device	Zum Aufschnappen auf Sammelschienensystem Rittal 60 mm
Design of the product	3-pole
Busbar design	Sammelschienendicke 5 oder 10 mm
Design of the operating mechanism	handle unit
Type of the driving mechanism / motor drive	No
Design of the safety monitoring	elektronisch EFM20
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Number of changeover contacts / for auxiliary contacts	0
Design of the load switch / Strip form	No
Product equipment / interlock	Yes

Product feature / sealable		Yes
Product component		
• phase failure monitoring		Yes
• undervoltage release mechanism		No
• undervoltage release with leading contact		No
• trip indicator		Yes
Acceptability for application		
• switch disconnecter		Yes
• emergency stop switch		No
• main switch		No
• safety cut-out switch		Yes
• maintenance/repair switch		Yes
Product function		
• fuse monitoring		Yes
• overvoltage protection monitoring		Yes
Product extension		
• auxiliary switch		Yes
• optional		
• voltage trigger		No
• locking capability		Yes
• motor drive		No
Continuous current		
• rated value	A	250
• at 35 °C / rated value	A	250
• at 40 °C / rated value	A	245
• at 45 °C / rated value	A	240
• at 50 °C / rated value	A	233
• at 55 °C / rated value	A	233
Operating current		
• at AC-21 B		
• at 400 V / rated value	A	250
• at 500 V / rated value	A	250
• at 690 V / rated value	A	250
• at AC-22 B		
• at 400 V / rated value	A	250
• at 500 V / rated value	A	250
• at 690 V / rated value	A	250
• at AC-23 B		
• at 400 V / rated value	A	250
• at 500 V / rated value	A	200

• at 690 V / rated value	A	100
• with capacitive load		
• at 400 V / maximum	A	72
• at 500 V / maximum	A	55
Let-through current		
• with speedy activation / maximum permissible	kA	25
• with closed switch / maximum permissible	kA	32
Conditional short-circuit current (I_q)		
• rated value	kA	80
• at 500 V / with AC / with speedy activation / rated value	kA	80
• at 690 V / with AC / with speedy activation / rated value	kA	50
• with closed switch		
• at 500 V / with AC / rated value	kA	120
• at 690 V / with AC / rated value	kA	100
Tension d'emploi		
• for AC / rated value	V	230 ... 690
Power factor		
• at AC-21 B		0.95
• at AC-22 B		0.65
• at AC-23 B		0.45
• with capacitive load		-0.25
Active power loss / maximum	W	23
Insulation voltage / rated value	V	690
Impulse voltage resistance / rated value	kV	8
I_{2t} value / with closed switch / maximum permissible	kA ² ·s	780
Item designation		
• according to DIN EN 61346-2		Q
• according to DIN EN 81346-2		Q

Connection elements and terminals:

Design of the electrical connection / for main current circuit		flat connector
Conductor cross section that can be connected / for main contacts		
• single- or multi-stranded	mm ²	16 ... 150
• stranded	mm ²	16 ... 150
Tightening torque		
• with screw-type terminals	N·m	10 ... 12
Arrangement of electrical connectors / for main current circuit		sonstige

Degree of protection and safety class:

Protection class IP		
----------------------------	--	--

• open	IP20
• on the front	IP40
• with closed switch	
• without cover or cable lug cover	IP30
• with cover or cable lug cover	IP40
Degree of pollution	3
Mechanical operating cycles as operating time / typical	1,600

Ambient conditions:

Ambient temperature

• during operating	°C	-25 ... +55
• during storage	°C	-50 ... +80

Installation/mounting/dimensions:

Mounting type

• rail mounting	busbar mounting
• front mounting	Yes
• front mounting with central attachment	No
• front mounting with 4-hole attachment	No
• floor mounting	No

mounting position

waagrecht oder senkrecht

Width

mm 183.7

Height

mm 306

Depth

mm 169.3

Largeur

• du jeu de barres	mm	12 ... 30
--------------------	----	-----------

Center line spacing

mm 60

Net weight

kg 2.99

Certificates/approvals:

General Product Approval

Declaration of Conformity

Test Certificates





[Type Test
Certificates/Test
Report](#)

Shipping Approval



Further information:





last change:

Jul 7, 2014