

FUSE-SWITCH-DISCONNECTOR I=160A, U=690V, 3-POLE
AUX.SWITCH 1NO + 1 NC FOR CABLE-LUG CONNECTION WITH
FUSE MONITORING BY 3RV, WITH AUX.SWITCH 2NO FUSE SIZE
NH00 W/3 METER CONNECTION CABLE



Figure similar

Certificates

General Product Approval	Declaration of Conformity	Test Certificates	other	
 CCC	 EG-Konf.	spezielle Prüfbescheinigungen n	Bestätigungen	sonstig

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3NP5060-0EA26-Z A02>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3NP5060-0EA26-Z A02/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3NP5060-0EA26-Z A02

CAX-Online-Generator
<http://www.siemens.com/cax>

Tender specifications
<http://www.siemens.com/specifications>