



DIRECT START, AC 400V, SZ. S00,
 2.2...3,2A,
 100V 50HZ / 100 ... 110V 60HZ SPRING-LOADED
 CONNECTION FOR DIN RAIL MOUNTING,
 TYPE OF ASSIGNMENT 2, IQ = 150KA (ALSO FULFILLS
 TYPE OF ASSIGNMENT 1) 1NO (CONTACTOR) COIL
 WITH RC ELEMENT ON FRONT PLUGGED ON
 (CONTACTOR) 1NO+1NC (CIRCUIT BREAKER,
 TRANSVERSE)

Allgemeine technische Daten:

product brand name		SIRIUS
Product designation		non-fused load feeders 3RA2
Size of the load feeder		S00
Number of poles / for main current circuit		3
Installation altitude / at a height over sea level / maximum	m	2,000
Product function		
• short circuit protection		Yes
• overload protection		Yes
• phase disturbance recognition		Yes
Product component		
• trip indicator		No
• auxiliary switch		Yes
Product extension / auxiliary switch		Yes
Design of display / for switching status		Switch setting
Insulation voltage / with degree of pollution 3 / rated value	V	690
Impulse voltage resistance / rated value	kV	6
Protection class IP		
• on the front		IP20
Protection against electrical shock		finger-safe

Shock resistance / according to IEC 60068-2-27		6g / 11 ms
maximum permissible voltage for safe isolation in networks with non-grounded star point		
Ambient temperature	°C	
• during transport		-50 ... +80
• during storage		-50 ... 80
• during operating		-20 ... 60
Manufacturer article number		
• of the circuit-breakers included in the scope of supply		3RV2011-1DA25
• of the contactor included in the scope of supply		3RT2015-2EG61
• of the RS applied assembly kit		
• of the link module included in the scope of supply		3RA2911-2AA00
• of the busbar adapter included in the scope of supply		
• of the RH applied assembly kit		

Hauptstromkreis:

Operating current / rated value	A	16
Mechanical operating cycles as operating time / of the auxiliary contacts / typical		30,000,000
Derating factor for rated value of the operational current		
Operating voltage / rated value	V	690
Voltage type / for main circuit		AC
Frequency		-
Service power / at AC-3	W	
• at 400 V / rated value		1,100
• at 500 V rated value		1,500
• at 690 V rated value		2,200
Operating current / at AC-3 / at 400 V / rated value	A	2.7
Type of assignment		2

Steuerstromkreis/ Ansteuerung:

Voltage type / for auxiliary and control circuit		AC
Control supply voltage / at 60 Hz / at AC	V	
• rated value		100 ... 110
Apparent holding power / of the solenoid / for AC	V·A	4.8

Hilfsstromkreis:

Design of the auxiliary switch		transverse
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		2
Number of changeover contacts / for auxiliary contacts		0

Schutz-/Überwachungsfunktion:		
Design of the overload circuit breaker		thermal (bimetallic)
Trip class		CLASS 10
Adjustable response current / of the current-dependent overload release	A	2.2 ... 3.2
Design of the short-circuit trip		magnetic
Conditional short-circuit current (I_q)	A	153,000
<ul style="list-style-type: none"> • at 400 V / according to IEC 60947-4-1 / rated value • at 690 V according to IEC 60947-4-1 rated value 		-
Varification of suitability / ATEX		Yes

Sicherheitsrelevante Kenngrößen:		
Proportion of dangerous failures		
<ul style="list-style-type: none"> • with high demand rate / according to SN 31920 	%	73
B10 value / with high demand rate / according to SN 31920		1,000,000

Einbau/ Befestigung/ Abmessungen:		
Mounting type		screw and snap-on mounting onto 35 mm standard mounting rail
mounting position		vertical
Depth	mm	155.1
Height	mm	197.6
Width	mm	45
Distance, to be maintained, to the ranks assembly		
<ul style="list-style-type: none"> • upwards 	mm	20
<ul style="list-style-type: none"> • forwards 	mm	0
<ul style="list-style-type: none"> • sideways 		0
<ul style="list-style-type: none"> • backwards 		0
<ul style="list-style-type: none"> • downwards 		30

Anschlüsse/ Klemmen:		
Arrangement of electrical connectors / for main current circuit		from front
Design of the electrical connection		
<ul style="list-style-type: none"> • for main current circuit 		spring-loaded terminals
<ul style="list-style-type: none"> • for auxiliary and control current circuit 		spring-loaded terminals
Type of the connectable conductor cross-section for main contacts		
<ul style="list-style-type: none"> • solid or multi-stranded 		2x (0,5 ... 4 mm ²)
<ul style="list-style-type: none"> • finely stranded 		
<ul style="list-style-type: none"> • with conductor end processing 		2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²)
<ul style="list-style-type: none"> • without conductor final cutting 		2x (0.5 ... 2.5 mm ²)

Type of connectable conductor cross-sections for auxiliary contacts <ul style="list-style-type: none"> • solid or multi-stranded • finely stranded <ul style="list-style-type: none"> • with conductor end processing • without conductor final cutting 		2x (0,5 ... 4 mm ²) 2x (0.5 ... 2.5 mm ²) 2x (0.5 ... 2.5 mm ²)
Type of the connectable conductor cross-section / for AWG conductors <ul style="list-style-type: none"> • for main contacts • for auxiliary contacts 		2x (20 ... 12) 2x (20 ... 16), 2x (18 ... 14)
Design of the thread of the connection screw for main contacts		
Design of the thread of the connection screw of the auxiliary and control pins		

UL/CSA Bemessungsdaten:


yielded mechanical performance [hp] / for three-phase squirrel cage motors <ul style="list-style-type: none"> • at 200/208 V / rated value • at 220/230 V / rated value • at 460/480 V rated value • at 575/600 V rated value 	hp hp 	0.5 0.75 1.5 2
Full-load current (FLA) / for 3-phase motor <ul style="list-style-type: none"> • at 480 V / rated value 	A	3.2


Approbationen/ Zertifikate:

General Product Approval	For use in hazardous locations	Declaration of Conformity		
 CSA		 UL	 ATEX	 EG-Konf.
Test Certificates	Shipping Approval			
Special Test Certificate	Type Test Certificates/Test Report	 ABS	 PRS	 RINA
other				
other	Environmental Confirmations			

Weitere Informationen:

Information- and Downloadcenter (Kataloge, Broschüren,...)
<http://www.siemens.de/industrial-controls/catalogs>





letzte Änderung:

Jul 28, 2014