

LOAD FEEDER FUSELESS REVERSING DUTY,  
AC 400V, SZ S0, 14. . .20A,  
AC 230V SCREW CONNECTION FOR RAIL-MOUNTING,  
W. DIN RAIL ADAPTER TYPE OF COORDINATION 2,  
IQ = 150KA (ALSO FULFILLS TYPE OF COORDINATION 1)  
1NO+1NC (CONTACTOR)

### Allgemeine technische Daten:

|                                                               |    |                             |
|---------------------------------------------------------------|----|-----------------------------|
| product brand name                                            |    | SIRIUS                      |
| Product designation                                           |    | non-fused load feeders 3RA2 |
| Size of the load feeder                                       |    | S0                          |
| Number of poles / for main current circuit                    |    | 3                           |
| Installation altitude / at a height over sea level / maximum  | m  | 2,000                       |
| Product function                                              |    |                             |
| • short circuit protection                                    |    | Yes                         |
| • overload protection                                         |    | Yes                         |
| • phase disturbance recognition                               |    | Yes                         |
| Product component                                             |    |                             |
| • trip indicator                                              |    | No                          |
| • auxiliary switch                                            |    | No                          |
| Product extension / auxiliary switch                          |    | Yes                         |
| Design of display / for switching status                      |    | Switch setting              |
| Insulation voltage / with degree of pollution 3 / rated value | V  | 690                         |
| Impulse voltage resistance / rated value                      | kV | 6                           |
| Protection class IP                                           |    |                             |
| • on the front                                                |    | IP20                        |
| Protection against electrical shock                           |    | finger-safe                 |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |    |                                                                                                                                                                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Shock resistance / according to IEC 60068-2-27</b>                                                                                                                                                                                                                                                                                                                                                                                                                                            |    | 6g / 11 ms                                                                                                                                                       |
| <b>maximum permissible voltage for safe isolation in networks with non-grounded star point</b>                                                                                                                                                                                                                                                                                                                                                                                                   |    |                                                                                                                                                                  |
| <b>Ambient temperature</b> <ul style="list-style-type: none"> <li>during transport</li> <li>during storage</li> <li>during operating</li> </ul>                                                                                                                                                                                                                                                                                                                                                  | °C | -50 ... +80<br>-50 ... 80<br>-20 ... 60                                                                                                                          |
| <b>Manufacturer article number</b> <ul style="list-style-type: none"> <li>of the standard mounting rail adapter included in the scope of supply</li> <li>of the circuit-breakers included in the scope of supply</li> <li>of the contactor included in the scope of supply</li> <li>of the RS applied assembly kit</li> <li>of the link module included in the scope of supply</li> <li>of the busbar adapter included in the scope of supply</li> <li>of the RH applied assembly kit</li> </ul> |    | <a href="#">3RA2922-1AA00</a><br><a href="#">3RV2021-4BA10</a><br><a href="#">3RT2027-1AP00</a><br><a href="#">3RA2921-1AA00</a><br><a href="#">3RA2923-1BB1</a> |

#### Hauptstromkreis:

|                                                                                                                                                                     |   |                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---------------------------|
| <b>Operating current / rated value</b>                                                                                                                              | A | 32                        |
| <b>Mechanical operating cycles as operating time / of the auxiliary contacts / typical</b>                                                                          |   | 10,000,000                |
| <b>Derating factor for rated value of the operational current</b>                                                                                                   |   |                           |
| <b>Operating voltage / rated value</b>                                                                                                                              | V | 690                       |
| <b>Voltage type / for main circuit</b>                                                                                                                              |   | AC                        |
| <b>Frequency</b>                                                                                                                                                    |   | -                         |
| <b>Service power / at AC-3</b> <ul style="list-style-type: none"> <li>at 400 V / rated value</li> <li>at 500 V rated value</li> <li>at 690 V rated value</li> </ul> | W | 7,500<br>11,000<br>15,000 |
| <b>Operating current / at AC-3 / at 400 V / rated value</b>                                                                                                         | A | 15.5                      |
| <b>Type of assignment</b>                                                                                                                                           |   | 2                         |

#### Steuerstromkreis/ Ansteuerung:

|                                                          |     |     |
|----------------------------------------------------------|-----|-----|
| <b>Voltage type / for auxiliary and control circuit</b>  |     | AC  |
| <b>Apparent holding power / of the solenoid / for AC</b> | V·A | 9.8 |

#### Hilfsstromkreis:

|                                                               |  |   |
|---------------------------------------------------------------|--|---|
| <b>Number of NC contacts / for auxiliary contacts</b>         |  | 1 |
| <b>Number of NO contacts / for auxiliary contacts</b>         |  | 1 |
| <b>Number of changeover contacts / for auxiliary contacts</b> |  | 0 |

#### Schutz-/Überwachungsfunktion:

|                                                                                                                                                                                                                                |   |                      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|----------------------|
| <b>Design of the overload circuit breaker</b>                                                                                                                                                                                  |   | thermal (bimetallic) |
| <b>Trip class</b>                                                                                                                                                                                                              |   | CLASS 10             |
| <b>Adjustable response current / of the current-dependent overload release</b>                                                                                                                                                 | A | 14 ... 20            |
| <b>Design of the short-circuit trip</b>                                                                                                                                                                                        |   | magnetic             |
| <b>Conditional short-circuit current (I<sub>q</sub>)</b><br><ul style="list-style-type: none"> <li>• at 400 V / according to IEC 60947-4-1 / rated value</li> <li>• at 690 V according to IEC 60947-4-1 rated value</li> </ul> | A | 153,000<br>-         |
| <b>Varification of suitability / ATEX</b>                                                                                                                                                                                      |   | Yes                  |

#### Sicherheitsrelevante Kenngrößen:

|                                                                                                                                              |   |           |
|----------------------------------------------------------------------------------------------------------------------------------------------|---|-----------|
| <b>Proportion of dangerous failures</b><br><ul style="list-style-type: none"> <li>• with high demand rate / according to SN 31920</li> </ul> | % | 73        |
| <b>B10 value / with high demand rate / according to SN 31920</b>                                                                             |   | 1,000,000 |

#### Einbau/ Befestigung/ Abmessungen:

|                                                                                                                                                                                                           |                          |                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------|
| <b>Mounting type</b>                                                                                                                                                                                      |                          | On adapter for screw and snap-on mounting on 35 mm standard mounting rail |
| <b>mounting position</b>                                                                                                                                                                                  |                          | vertical                                                                  |
| <b>Depth</b>                                                                                                                                                                                              | mm                       | 120.3                                                                     |
| <b>Height</b>                                                                                                                                                                                             | mm                       | 265                                                                       |
| <b>Width</b>                                                                                                                                                                                              | mm                       | 90                                                                        |
| <b>Distance, to be maintained, to the ranks assembly</b><br><ul style="list-style-type: none"> <li>• upwards</li> <li>• forwards</li> <li>• sideways</li> <li>• backwards</li> <li>• downwards</li> </ul> | mm<br>mm<br><br><br><br> | 30<br>10<br>0<br>0<br>30                                                  |

#### Anschlüsse/ Klemmen:

|                                                                                                                                                                                                                             |  |                                                                                                  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------|
| <b>Arrangement of electrical connectors / for main current circuit</b>                                                                                                                                                      |  | from the top                                                                                     |
| <b>Design of the electrical connection</b><br><ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control current circuit</li> </ul>                                             |  | screw-type terminals<br>screw-type terminals                                                     |
| <b>Type of the connectable conductor cross-section for main contacts</b><br><ul style="list-style-type: none"> <li>• solid or multi-stranded</li> <li>• finely stranded</li> <li>• with conductor end processing</li> </ul> |  | 2x (1 ... 2,5 mm²), 2x (2,5 ... 10 mm²)<br><br>2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²), 1x 10 mm² |
| <b>Type of connectable conductor cross-sections for auxiliary contacts</b><br><ul style="list-style-type: none"> <li>• solid or multi-stranded</li> </ul>                                                                   |  | 2x (0,5 ... 1,5 mm²), 2x (0,75 ... 2,5 mm²)                                                      |

|                                                                                                                                                                                 |     |                                                                       |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>finely stranded</li> <li>with conductor end processing</li> </ul>                                                                        |     | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ) |
| <b>Type of the connectable conductor cross-section / for AWG conductors</b> <ul style="list-style-type: none"> <li>for main contacts</li> <li>for auxiliary contacts</li> </ul> |     | 2x (16 ... 12), 2x (14 ... 8)<br>2x (20 ... 16), 2x (18 ... 14)       |
| <b>Tightening torque / for main contacts</b> <ul style="list-style-type: none"> <li>with screw-type terminals</li> </ul>                                                        | N·m | 2 ... 2.5                                                             |
| <b>Design of the thread of the connection screw for main contacts</b>                                                                                                           |     |                                                                       |
| M4                                                                                                                                                                              | M4  |                                                                       |
| <b>Tightening torque / for auxiliary contacts</b> <ul style="list-style-type: none"> <li>with screw-type terminals</li> </ul>                                                   | N·m | 0.8 ... 1.2                                                           |
| <b>Design of the thread of the connection screw of the auxiliary and control pins</b>                                                                                           |     |                                                                       |
| M3                                                                                                                                                                              | M3  |                                                                       |
| <b>Dimension de la tête de tournevis</b>                                                                                                                                        |     | Pozidriv 2                                                            |

#### UL/CSA Bemessungsdaten:

yielded mechanical performance [hp] / for three-phase squirrel cage motors

- at 460/480 V rated value
- at 575/600 V rated value

#### Approbationen/ Zertifikate:

General Product Approval

For use in hazardous locations

Declaration of Conformity

Test Certificates



[Type Test Certificates/Test Report](#)

#### Shipping Approval



other

[other](#)

[Environmental Confirmations](#)


#### Weitere Informationen:


Information- and Downloadcenter (Kataloge, Broschüren,...)

<http://www.siemens.de/industrial-controls/catalogs>

Industry Mall (Online-Bestellsystem)

<http://www.siemens.de/industrial-controls/mall>





letzte Änderung:

Jul 28, 2014