

ENABLING MODULE FOR OPERATOR PANEL 3RA69350A

General technical data:

product brand name		SIRIUS
Product designation		dongle
Protection class IP		IP20
Relative humidity		
• during operating phase	%	10 ... 90
Ambient temperature		
• during transport	°C	-55 ... +80
• during storage	°C	-55 ... +80
• during operating	°C	-20 ... +60
Reference code		
• according to DIN EN 61346-2		T
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		T

Installation/ mounting/ dimensions:

Width	mm	18
Height	mm	16
Depth	mm	10

Certificates/ approvals:

Verification of suitability	IEC / EN 60947-6-2
-----------------------------	--------------------

General Product Approval

EMC



Shipping Approval



other

[Declaration of Conformity](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RA6936-0A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RA6936-0A

last change:

Jul 7, 2014