

OVERLOAD RELAY 50...200 A FOR MOTOR
PROTECTION SIZE S6,
CLASS 10 MOUNT. ONTO CONT./ STAND-ALONE MAIN
CIRCUIT: BAR CONNECTION AUX. CIRCUIT:
SPRINGLOAD. TERM. MANUAL-AUTOMATIC-RESET

General technical data:

product brand name		SIRIUS
Product designation		solid-state overload relay
Size of overload relay		S6
Number of poles / for main current circuit		3
Product function / removable terminal for auxiliary and control circuit		Yes
Impulse voltage resistance / rated value	kV	8
Protection class IP		IP20
Protection class IP / on the front		IP20
Protection against electrical shock		finger-safe with cover
Installation altitude / at a height over sea level / maximum	m	2,000
Resistance against shock		15g / 11 ms
Ambient temperature		
• during transport	°C	-40 ... +80
• during storage	°C	-40 ... +80
• during operating	°C	-25 ... +60
Relative humidity / during operating phase / maximum	%	100
Electrostatic discharge / according to IEC 61000-4-2		6 kV contact discharge / 8 kV air discharge
Field-bound parasitic coupling / according to IEC 61000-4-3		10 V/m
Conductor-bound parasitic coupling BURST / according to IEC 61000-4-4		2 kV (power ports), 1 kV (signal ports) corresponds to degree of severity 3
Conductor-bound parasitic coupling conductor-earth SURGE / according to IEC 61000-4-5		2 kV (line to earth) corresponds to degree of severity 3
Conductor-bound parasitic coupling conductor-conductor SURGE / according to IEC 61000-4-5		1 kV (line to line) corresponds to degree of severity 3
Type of protection		PTB 06 ATEX 3001 Ex II (2) GD
Active power loss / total / typical	W	0.05
Size of the contactor / can be combined / company-specific		S6

Main circuit:

Operating current / of the fuse link / rated value	A	315
--	---	-----

Type of assignment		2
--------------------	--	---

Auxiliary circuit:		
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1
Number of changeover contacts / for auxiliary contacts		0
Design of the fuse link / for short-circuit protection of the auxiliary switch / required		fuse gL/gG: 6 A
Operating current / of the auxiliary contacts		
• at AC-15		
• at 24 V	A	4
• at 110 V	A	4
• at 120 V	A	4
• at 125 V	A	4
• at 230 V	A	3
• at DC-13		
• at 24 V	A	2
• at 60 V	A	0.55
• at 110 V	A	0.3
• at 125 V	A	0.3
• at 220 V	A	0.11

Protective and monitoring functions:		
Trip class		CLASS 10
Adjustable response current / of the current-dependent overload release	A	50 ... 200

Installation/ mounting/ dimensions:		
Mounting type		direct mounting / stand-alone installation
mounting position		any
Depth	mm	155
Height	mm	119
Width	mm	120

Connections/ terminals:		
Design of the electrical connection		
• for main current circuit		busbar connection
• for auxiliary and control current circuit		spring-loaded terminals
Type of the connectable conductor cross-section		
• for auxiliary contacts		
• solid		2x (0.25 ... 1.5 mm²)
• finely stranded		

- 2x (0.25 ... 1.5 mm²)
2x (24 ... 16)

General Product Approval	EMC	For use in hazardous locations
---------------------------------	------------	---------------------------------------

For use in hazardous locations



ATEX

<u>Special Test</u> <u>Certificate</u>	<u>Type Test</u> <u>Certificates/Test</u> <u>Report</u>
1. <u>Special Test</u> 2. <u>Certificate</u>	1. <u>Type Test</u> 2. <u>Certificates/Test</u> 3. <u>Report</u>

RINA

<u>Declaration of</u>	<u>other</u>	<u>Environmental</u>
<u>Conformity</u>		<u>Confirmations</u>


<http://www.siemens.com/industrial-controls/catalogs>

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/cax>

<http://support.automation.siemens.com/WW/view/en/3RB2056-1FF2/all>

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RB2056-1FF2



last change:

Jun 16, 2014