



OVERLOAD RELAY 10...40 A FOR MOTOR PROTECTION
SIZE S0,
CLASS 5...30 CONTACTOR ASS. MAIN CIRCUIT: SCREW
CONN. AUX.CIRCUIT: SCREW CONN. MANUAL-AUTOM.-
RESET INT. GROUND FAULT DETECTION

General technical data:

product brand name		SIRIUS
Product designation		solid-state overload relay
Size of overload relay		S0
Number of poles / for main current circuit		3
Product function / removable terminal for auxiliary and control circuit		Yes
Product function		
• overload protection		Yes
• phase disturbance recognition		Yes
• short-circuit to earth recognition		Yes
Product component		
• auxiliary switch		Yes
• trip indicator		Yes
Insulation voltage / with degree of pollution 3 / rated value	V	690
Impulse voltage resistance / rated value	kV	6
Protection class IP		
• of the terminal		IP20
• on the front		IP20
Protection against electrical shock		finger-safe

Installation altitude / at a height over sea level / maximum	m	2,000
Resistance against vibration		1-6 Hz, 15 mm; 6-500 Hz, 20 m/s²; 10 cycles
Ambient temperature		
• during transport	°C	-40 ... +80
• during storage	°C	-40 ... +80
• during operating	°C	-25 ... +60
Relative humidity		
• during operating phase	/ %	95
EMC immunity to interference / according to IEC 60947-1		corresponds to degree of severity 3
EMC emitted interference / according to IEC 60947-1		CISPR 11, environment B (residential area)
Electrostatic discharge / according to IEC 61000-4-2		6 kV contact discharge / 8 kV air discharge
Field-bound parasitic coupling / according to IEC 61000-4-3		10 V/m
Conductor-bound parasitic coupling BURST / according to IEC 61000-4-4		2 kV (power ports), 1 kV (signal ports) corresponds to degree of severity 3
Conductor-bound parasitic coupling conductor-earth SURGE		2 kV (line to earth) corresponds to degree of severity 3
Conductor-bound parasitic coupling conductor-conductor SURGE		1 kV (line to line) corresponds to degree of severity 3
Type of protection		PTB 09 ATEX 3001 Ex II (2) G [Ex e] [Ex d] [Ex px] D [Ex tj] [Ex p]
Active power loss / total / typical	W	3
Size of the contactor / can be combined / company-specific		S0

Main circuit:

Operating current		
• at AC-3 / at 400 V / rated value	A	40
• of the auxiliary contacts		
• at AC-15		
• at 24 V	A	4
• at 110 V	A	4
• at 120 V	A	4
• at 125 V	A	4
• at 230 V	A	3
• at DC-13		
• at 24 V	A	2
• at 60 V	A	0.55
• at 110 V	A	0.3
• at 125 V	A	0.3
• at 220 V	A	0.11
Type of assignment		2

Control circuit/ Control:

Type of voltage supply / via input/ output link master		No
Voltage type / for auxiliary and control circuit		AC/DC

Auxiliary circuit:

Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		1
Number of changeover contacts / for auxiliary contacts		0
Design of the fuse link / for short-circuit protection of the auxiliary switch / required		fuse gL/gG: 6 A

Protective and monitoring functions:

Trip class		CLASS 5, 10, 20 and 30 adjustable
Adjustable response current		
of the current-dependent overload release	A	10 ... 40

Installation/ mounting/ dimensions:

Mounting type		direct mounting
mounting position		any
Depth	mm	84
Height	mm	87
Width	mm	45
Arrangement of electrical connectors / for main current circuit		Top and bottom

Connections/ terminals:

Design of the electrical connection		
for main current circuit		screw-type terminals
for auxiliary and control current circuit		screw-type terminals
Type of the connectable conductor cross-section		
- for main contacts - solid or multi-stranded		1x (1 ... 10 mm ²), 2x (1 ... 10 mm ²)
- finely stranded - with conductor end processing		1x (1 ... 6 mm ²), 2 x (1 ... 6 mm ²), 1x 10 mm ²
for AWG conductors / for main contacts		1x (16 ... 8), 2x (16 ... 8)
- for auxiliary contacts - solid or multi-stranded		1x (0,5 ... 4 mm ²), 2x (0,5 ... 1,5 mm ²), 2x (0,75 ... 2,5 mm ²)
- finely stranded - with conductor end processing		1x (0.5 ... 1.5 mm ²), 2x (0.5 ... 1.5 mm ²), 1x (0.5 ... 2.5 mm ²)
for AWG conductors / for auxiliary contacts		1x (20 ... 14), 2x (20 ... 14)

UL/CSA ratings:

Contact rating designation / for auxiliary contacts / according to UL

B300 / R300

Certificates/ approvals:

General Product Approval

EMC

For use in
hazardous
locations



CCC



CSA



UL



C-TICK



ATEX

Test Certificates

[Special Test
Certificate](#)

[Type Test
Certificates/Test
Report](#)

Shipping Approval



ABS



BUREAU
VERITAS



GL



LRS



RINA

other

[Declaration of
Conformity](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator



<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RB3123-4VB0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RB3123-4VB0



last change:

Aug 4, 2014