



SOLID-STATE CONTACTOR 3-PH 3RF3 AC53 3.8A 40 DEGREES C 48-480V / 24V DC REVERSE SWITCHING INSTANTANEOUS SCREW TERMINALS

General technical data:		
product brand name		SIRIUS
product designation		solid-state reversing contactor
• _1 / of the accessories that can be ordered		Link module
• _2 / of the accessories that can be ordered		Connection adapter
Manufacturer article number		
• _1 / of the accessories that can be ordered		3RA2921-1BA00
• _2 / of the accessories that can be ordered		3RF3900-0QA88
Protection class IP		IP20
Insulation voltage / rated value	V	600
Installation altitude / at a height over sea level / maximum	m	1,000
Ambient temperature		
• during storage	°C	-55 ... +80
• during operating	°C	-25 ... +60
Resistance against shock		
• according to IEC 60068-2-27		15g / 11 ms
Resistance against vibration		
• according to IEC 60068-2-6		2g
Resistance against the impulse current / rated value	A	600
Active power loss / total / typical	W	7

Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		K
		Q
Product function		reversing switch

Main circuit:

Number of poles / for main current circuit		3
Number of NC contacts / for main contacts		0
Number of NO contacts / for main contacts		2
Operating frequency • rated value	Hz	60 ... 50
Operating voltage • at 60 Hz / at AC / rated value • at 50 Hz / at AC / rated value	V	48 ... 480
	V	48 ... 480
Operating current • minimum • at AC-3 / at 400 V / rated value	mA	500
	A	3.8
Working area related to the operating voltage • at 50 Hz / for AC • at 60 Hz / for AC	V	40 ... 506
	V	40 ... 506
Service power / at AC-3 / at 400 V • rated value	kW	1.5
Derating temperature	°C	40
Tolerance of the line frequency	Hz	5
Relative symmetrical tolerance / of the operation frequency	%	10
I²t-level / maximum	A ² ·s	1,800
Voltage slew rate / at the thyristor / for main contacts • maximum permissible	V/μs	1,000
Block voltage / at the thyristor / for main contacts • maximum permissible	V	1,200
Reverse current / of the thyristor	mA	10

Control circuit:

Type of voltage / of the controlled supply voltage		DC
Control supply voltage • 1 • for DC • initial rated value • final rated value • for DC / final value for signal<0>-recognition		
	V	15
	V	30
	V	5

Control current • for DC / rated value • at minimum control supply voltage / for DC	mA	15
	mA	2

Auxiliary circuit:		
Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		0
Number of change-over switches / for auxiliary contacts		0

Installation/mounting/dimensions:		
mounting position		vertical
Type of mounting		screw and snap-on mounting onto 35 mm standard mounting rail
Type of fixing/fixation / series installation		Yes
Tightening torque / of the screw for fastening of the operating resource	N·m	1.5
Design of the thread / of the screw for fastening of the operating resource		M4
Width	mm	45
Height	mm	95
Depth	mm	114.3
Distance, to be maintained, to the ranks assembly • upwards • downwards	mm	70
	mm	50

Connections:		
Design of the electrical connection • for main current circuit • for auxiliary and control current circuit		screw-type terminals
		screw-type terminals
Design of the thread / of the connection screw • for main contacts • of the auxiliary and control pins		M4
		M3
Product function / removable terminal for auxiliary and control circuit		Yes
Type of the connectable conductor cross-section • for main contacts • solid • finely stranded • with conductor end processing • for AWG conductors / for main contacts • for auxiliary and control contacts • solid		2x (1.5 ... 2.5 mm²), 2x (2.5 ... 6 mm²)
		2x (1 ... 2.5 mm²), 2x (2.5 ... 6 mm²), 1x 10 mm²
		2x (14 ... 10)
		1x (0.5 ... 2.5 mm²), 2x (0.5 ... 1.0 mm²)

- finely stranded - with conductor end processing - without conductor final cutting - for AWG conductors / for auxiliary and control contacts		1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (AWG 20 ... 12)
Tightening torque		
- for main contacts / with screw-type terminals - for auxiliary and control contacts / with screw-type terminals	N·m	2 ... 2.5
	N·m	0.5 ... 0.6
Tightening torque (lbf·in)		
- for main contacts / with screw-type terminals - for auxiliary and control contacts / with screw-type terminals	lbf·in	18 ... 22
	lbf·in	7.5 ... 5.3
Skinning length / of the cable		
- for main contacts - for auxiliary and control contacts	mm	10
	mm	7

Certificates/approvals:

Verification of suitability

CE / UL / CSA / CCC / C-TICK

General Product Approval

EMC

Declaration of Conformity



CSA

GOST

UL

C-TICK

EG-Konf.

UL/CSA ratings

yielded mechanical performance (hp) / for three-phase squirrel cage motors

- at 200/208 V / rated value
- at 220/230 V / rated value
- at 460/480 V / rated value

hp 0.5
hp 0.75
hp 2

Operating current (FLA) / for three-phase squirrel cage motors

- at 480 V / rated value

A 3.4

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator





<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RF3403-1BD04/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RF3403-1BD04



last change:

Feb 4, 2013