



AS-INTERFACE MODULE 4I/4O 4X1 INPUT,
FREE OF POTENTIAL 4X1 OUTPUT ELECTRON. DC
24V,2A COMBICON STRIPS WIDTH 90MM COMBICON
CONNECTOR SET 3RX9810-0AA00 TO BE ORDERED
SEPARATELY

General technical data:		
Design of the product		F90 module - I/O modules for operation in the control cabinet, IP20
Type		4 inputs / 4 outputs
Design of the slave type		standard slave
I/O configuration		7
ID/ID2 code		0/F
Design of the electrical connection / of the inputs and outputs		combicon connection
AS interface / total current input / max	mA	30
operating voltage • according to AS-Interface specification	V	26.5 ... 31.6
Addressing		possible using integrated addressing socket
Watchdog		built-in
Note 1		The module has four floating inputs and four floating switching outputs. An external additional supply of 20 to 30 V DC according to VDE 0106 (PELV) protection class III is required for the supply of the input and output circuits.
Note 2		An external additional supply (AUX POWER) of 20 to 30 V DC is required for the supply of the output circuits. The additional supply must comply with VDE 0106 (PELV), protection class III.

Sensor supply:		
Type of voltage supply / for the sensor supply		via AUX POWER
Characteristic feature of the sensor supply / short-circuit and overload resistant		Yes
Current carrying capacity / of the sensor supply / for all inputs / at ambient temperature 40 °C	mA	200

Inputs:		
Number of digital inputs		4
Type of connection		2- and 3-conductor PNP transistor, floating
Input circuit		PNP transistor
Type of / input voltages		DC
Input current / at the digital input		
• for signal <1> / minimum	mA	5
• at signal <0> / maximum	mA	1.5
Inputs		
• switching level High / min	V	10
• sensor supply using AS-Interface		short-circuit and overload resistant
• connection / sensors		2- and 3-conductor technology

Outputs:		
Number of digital outputs		4
Voltage type / of output voltages		DC
Outputs / external power supply 24 V DC		using Combicon plug connector
Output current / at the digital output / for signal <1> / nominal value	A	2
Design of the switching output		solid state
Outputs / total current / of all outputs	A	6
Characteristic feature of the output / short-circuit protected		Yes
Outputs		
• short-circuit protection		built-in
• induction protection		built-in

Status display		
• display of I/Os		yellow LEDs
• display of AS-Interface/diagnostics		green/red dual LED

Assignment of data bits		
• D0		IN1/OUT1
• D1		IN2/OUT2
• D2		IN3/OUT3
• D3		IN4/OUT4

Ambient conditions:

Ambient temperature

• during operating	°C	-25 ... +70
• during storage	°C	-40 ... +85

Protection class IP

IP20

Mechanical design:

Width	mm	90
Height	mm	75
Depth	mm	37
Mounting type		35 mm standard rail mounting

Certificates/approvals:

AS-Interface certificate

yes

Approvals

UL, CSA, shipbuilding

General Product Approval



Shipping Approval



other

[Confirmation](#)

[Declaration of
Conformity](#)

[other](#)

[Environmental
Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RG9004-ODC00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RG9004-ODC00

last change:

Jul 21, 2014