



COUPLING RELAY, 2NO+2NC, 52V DC,
0.7...1.25*US, W. VARISTOR,
SCREW CONNECTION, SIZE S00

General technical data:		
product brand name		SIRIUS
Product designation		Coupling relay for switching auxiliary circuits
Size of the contactor		S00
Protection class IP / on the front		IP20
Degree of pollution		3
Insulation voltage / with degree of pollution 3 / rated value	V	690
Installation altitude / at a height over sea level / maximum	m	2,000
Ambient temperature		
• during transport	°C	-55 ... +80
• during storage	°C	-55 ... +80
• during operating	°C	-25 ... +60
Contact reliability		one incorrect switching operation of 100 million switching operations (17 V, 1 mA)
Resistance against shock		10g / 5 ms and 5g / 10 ms
Impulse voltage resistance / rated value	kV	6
Reference code		
• according to DIN EN 61346-2		K
• according to DIN 40719 extended according to IEC 204-2 / according to IEC 750		K
• according to DIN EN 81346-2		K

Mechanical operating cycles as operating time			30,000,000
• of the contactor / typical			
Control circuit/ Control:			
Voltage type / of control feed voltage			DC
Control supply voltage			
• for DC / rated value	V		52
Operating range factor control supply voltage rated value / of the magnet coil			
• for DC			0.7 ... 1.25
Pull-in power / of the solenoid / for DC	W		2.3
Holding power / of the solenoid / for DC	W		2.3
Design of the surge suppressor			with varistor
Auxiliary circuit:			
Product extension / auxiliary switch			No
Identification number and letter for switching elements			22 E
Contact reliability / of the auxiliary contacts			1 faulty switching per 100 million (17 V, 1 mA)
Number of NC contacts / for auxiliary contacts			2
• delayed switching			0
• instantaneous switching			2
• asynchronous switching			0
• lagging switching			0
Number of NO contacts / for auxiliary contacts			2
• instantaneous switching			2
• delayed switching			0
• asynchronous switching			0
• leading switching			0
Number of changeover contacts			
• for auxiliary contacts			0
• of the auxiliary contacts / instantaneous switching			0
Operating current			
• at AC-12 / maximum	A		10
• at AC-15			
• at 230 V / rated value	A		6
• at 400 V / rated value	A		3
• at 500 V / rated value	A		2
• at 690 V / rated value	A		1
Operating current / with 1 current path			
• at DC-12			
• at 24 V / rated value	A		10

- at 110 V / rated value
- at 220 V / rated value
- at DC-13
 - at 24 V / rated value
 - at 110 V / rated value
 - at 220 V / rated value

A	3
A	1
A	10
A	1
A	0.27

Short-circuit:

Design of the fuse link / for short-circuit protection of the auxiliary switch / required

fuse gL/gG: 10 A

Installation/ mounting/ dimensions:

mounting position

+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface

Mounting type

screw and snap-on mounting

Width

mm 45

Height

mm 57.5

Depth

mm 72

Distance, to be maintained, to the ranks assembly / sideways

mm 0

Connections/ terminals:

Design of the electrical connection / for auxiliary and control current circuit

screw-type terminals

Type of the connectable conductor cross-section

- for auxiliary contacts
 - solid
 - finely stranded
 - with conductor end processing
- for AWG conductors / for auxiliary contacts

2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²

2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)

2x (20 ... 16), 2x (18 ... 14), 1x 12

Certificates/ approvals:

Verification of suitability

CSA / UL / CCC / GL / LRS / BV / DNV / RMRS / RINA

General Product Approval

Functional Safety / Safety of Machinery

Declaration of Conformity



CCC



CSA



UL

[Type Examination](#)



EG-Konf.

Test Certificates

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



ABS



BUREAU VERITAS



DNV



GL



LRS



PRS

Shipping Approval

other



RMRS

[other](#)

[Environmental Confirmations](#)

Safety related data:

Proportion of dangerous failures

- with high demand rate / according to SN 31920
- with low demand rate / according to SN 31920

%

75

%

40

Protection against electrical shock

finger-safe

T1 value / for proof test interval or service life / according to IEC 61508

a

20

B10 value / with high demand rate

- according to SN 31920
- note

1,000,000

With 0.3 x Ie

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/>

Cax online generator





<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RH1122-1KK80/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RH1122-1KK80



last change:

Jul 21, 2014