

CONTACTOR RELAY, 2NO+2NC, DC 24 V, CAGE CLAMP CONNECTION, SIZE S00 REUSABLE PACKING PACKING = 144 UNITS



Figure similar

product brand name	SIRIUS
Product designation	contactor relay
General technical data	
Size of contactor	S00
Product extension	
• Auxiliary switch	Yes
Insulation voltage	
• with degree of pollution 3 rated value	690 V
Degree of pollution	3
Surge voltage resistance rated value	6 kV
Protection class IP	
• on the front	IP20
Shock resistance	10g / 5 ms and 5g / 10 ms
Mechanical service life (switching cycles)	
• of contactor typical	30 000 000
• of the contactor with added electronics-compatible auxiliary switch block typical	5 000 000

• of the contactor with added auxiliary switch block typical	10 000 000
Equipment marking	
• acc. to DIN EN 61346-2	K
• acc. to DIN EN 81346-2	K
Ambient conditions	
Installation altitude at height above sea level maximum	2 000 m
Ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-55 ... +80 °C
• during transport	-55 ... +80 °C
Control circuit/ Control	
Type of voltage of the control supply voltage	DC
Control supply voltage at DC	
• rated value	24 V
Operating range factor control supply voltage rated value of magnet coil at DC	0.8 ... 1.1
Closing power of magnet coil at DC	3.2 W
Holding power of magnet coil at DC	3.2 W
Auxiliary circuit	
Number of NC contacts	
• for auxiliary contacts	2
— instantaneous contact	2
— delayed switching	0
— lagging switching	0
— make-before-break switching	0
Number of NO contacts	
• for auxiliary contacts	2
— instantaneous contact	2
— delayed switching	0
— leading contact	0
— make-before-break switching	0
Number of CO contacts	
• for auxiliary contacts	0
• of auxiliary contacts instantaneous contact	0
Identification number and letter for switching elements	22 E
Operating current at AC-12 maximum	10 A
Operating current at AC-15	
• at 230 V rated value	6 A

• at 400 V rated value • at 500 V rated value • at 690 V rated value	3 A 2 A 1 A
Operating current at 1 current path at DC-12 • at 24 V rated value • at 110 V rated value • at 220 V rated value	10 A 3 A 1 A
Operating current at 1 current path at DC-13 • at 24 V rated value • at 110 V rated value • at 220 V rated value	10 A 1 A 0.27 A
Contact reliability of auxiliary contacts	1 faulty switching per 100 million (17 V, 1 mA)

Short-circuit protection

Design of the fuse link • for short-circuit protection of the auxiliary switch required	fuse gL/gG: 10 A
--	------------------

Installation/ mounting/ dimensions

Mounting position	+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface
Mounting type	screw and snap-on mounting
Height	60 mm
Width	45 mm
Depth	73 mm
Required spacing • with side-by-side mounting — at the side	0 mm

Connections/Terminals

Type of electrical connection • for auxiliary and control current circuit	Cage Clamp terminals
Type of connectable conductor cross-sections • for auxiliary contacts — solid — finely stranded with core end processing — finely stranded without core end processing • at AWG conductors for auxiliary contacts	2x (0.25 ... 2.5 mm²) 2x (0.25 ... 1.5 mm²) 2x (0.25 ... 2.5 mm²) 2x (24 ... 14)

Safety related data

B10 value • with high demand rate acc. to SN 31920	1 000 000; With 0.3 x Ie
Proportion of dangerous failures	

- with low demand rate acc. to SN 31920
- with high demand rate acc. to SN 31920

40 %

75 %

T1 value for proof test interval or service life acc. to IEC 61508

20 y

Certificates/approvals

General Product Approval

Functional
Safety/Safety
of Machinery

Declaration of
Conformity



CCC



CSA



UL



[Baumusterbescheinigung](#)



EG-Konf.

Test Certificates

Shipping Approval

[spezielle
Prüfbescheinigung](#)

[Typprüfbescheinigung/Werkszeugnis](#)



ABS



BUREAU
VERITAS



DNV



GL

Shipping Approval

other



LRS



PRS



RINA



RMRS

[Umweltbestätigung](#)

[sonstig](#)

other

[Bestätigungen](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH1122-2BB40-Z X95>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH1122-2BB40-Z X95>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RH1122-2BB40-Z X95>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH1122-2BB40-Z X95&lang=en



last modified:

09/20/2016