





ASI-safe module, IP00, digital 2 F-DI + 4 DI/4 DO Dual slave for FORTRESS 2 x safe input, Cat. 1/2 or 1 x safe input Cat. 3/4 (Cat.: safety category according to EN 954-1) and 4 x standard input for IN-DATA from internal, serial bus, 4 x standard output for OUT-DATA to internal, serial bus, U_asi max. 270 mA in total via connector X320/5 V/max.250 mA to internal, serial bus Module occupies 2 AS-i addresses consisting of 3 PCBs without enclosure Connection AS-i via eyelets Connection internal, serial bus via connector X320/8-pole

Certificates/ approvals

General Product Approval		Marine / Shipping	other
	 EG-Konf.	Confirmation	
		 URS	Miscellaneous

other Environment

[Confirmation](#)

[Environmental Confirmations](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1405-0SD00-0BA0>
- Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1405-0SD00-0BA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RK1405-0SD00-0BA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1405-0SD00-0BA0&lang=en

last modified:

3/11/2024 