

AS-Interface distributor compact for AS-i profile cable IP 67/68/69K, max. 8 A



General technical data

Type of device		AS-Interface accessories
Function		distribution function for AS-i flat cables
operating voltage according to AS-Interface specification	V	26.5 ... 31.6
Note		cable must not end in the feeder
Note 1		cable must not end in a feeder

Connections/Terminals

connection		insulation piercing method for AS-Interface flat cable
Connection system		insulation piercing method for AS-Interface flat cable

Mechanical data

Type of mounting		screw fixing
Contacts Load rating max	A	8

Ambient conditions

Ambient temperature	°C	-25 ... +75
Ambient temperature during storage	°C	-25 ... +85
degree of protection		IP67/68/69K

Certificates/approvals

General Product Approval	Declaration of Conformity	Shipping Approval
 UL	 EAC	 EG-Konf.
	Miscellaneous	 ABS
		 PRS

Shipping Ap- proval	other
 RMRS	Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1901-2NN10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-2NN10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-2NN10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-2NN10&lang=en

last modified:

02/17/2019