

AS-Interface M12 branch U_ASI without Uaux, with M12 socket IP67/68/69K, max. 4 A



General technical data		
Type of device		AS-Interface accessories
Function		AS-i flat cable transition to M12
operating voltage according to AS-Interface specification	V	26.5 ... 31.6
Number sockets		1
Note		cable must not end in the feeder
Note 1		cable must not end in a feeder
Connections/Terminals		
connection		insulation piercing method for AS-Interface flat cable
Connection system		insulation piercing method for AS-Interface flat cable
Inputs		
Inputs socket assignment		1 = AS-i "+" 3=AS-i "-"
Mechanical data		
Type of mounting		screw fixing
Contacts Load rating max	A	4
Ambient conditions		
Ambient temperature	°C	-25 ... +75

Ambient temperature during storage	°C	-25 ... +85
degree of protection		IP67/68/69K

Certificates/approvals

General Product Approval		Declaration of Conformity	Shipping Approval		
 UL		 EG-Konf.	 ABS	 PRS	 RMRS

other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1901-2NR10>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1901-2NR10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1901-2NR10>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1901-2NR10&lang=en

last modified:

10/13/2018