



TERMINAL MODULE FOR ET 200S PMD FOR POWER
MODULE F. STARTER

General technical data:

Product designation		Terminal module
Product-type designation		TM-P15 S27-01
Design of the product		for power module PM-D, with end cover
Mounting height	mm	117.5
Installation width	mm	15
Mounting depth	mm	102
Protection class IP		IP20
Insulation voltage / rated value	V	500
Operating voltage		
• for DC / rated value	V	24
Operating current / rated value	A	10
Type of the connectable conductor cross-sections		
• solid		1x (0.14 ... 2.5 mm ²), acc. to IEC 60947
• finely stranded / with wire end processing		1x (0.14 ... 1.5 mm ²), acc. to IEC 60947
• for AWG conductors		
• solid		1x (18 ... 22)
• stranded		1x (18 ... 22)

Mounting/fixing:

Dimension de la tête de tournevis		Standard screwdriver Size 1
-----------------------------------	--	-----------------------------

Tightening torque

- with screw-type terminals

N·m

0.4 ... 0.7

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:



<http://www.siemens.com/cax>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RK1903-0AA00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RK1903-0AA00





last change:

Mar 5, 2013