

### TM-X15 S27-01 TERMINAL MODULE F. CONNECTION MODULE PM-X

#### General technical data:

|                                                  |    |                                                                         |
|--------------------------------------------------|----|-------------------------------------------------------------------------|
| Product designation                              |    | Terminal module                                                         |
| Product-type designation                         |    | TM-X15 S27-01                                                           |
| Design of the product                            |    | for connection module PM-X terminal unit for incoming feeder protection |
| Mounting height                                  | mm | 196.5                                                                   |
| Installation width                               | mm | 15                                                                      |
| Mounting depth                                   | mm | 102                                                                     |
| Protection class IP                              |    | IP20                                                                    |
| Insulation voltage / rated value                 | V  | 500                                                                     |
| Operating voltage                                |    |                                                                         |
| • for DC / rated value                           | V  | 24                                                                      |
| Operating current / rated value                  | A  | 10                                                                      |
| Type of the connectable conductor cross-sections |    |                                                                         |
| • solid                                          |    | 1x (0.14 ... 2.5 mm²)                                                   |
| • finely stranded / with wire end processing     |    | 1x (0.14 ... 1.5 mm²), acc. to IEC 60947                                |
| • for AWG conductors                             |    |                                                                         |
| • solid                                          |    | 1x (18 ... 22)                                                          |
| • stranded                                       |    | 1x (18 ... 22)                                                          |

#### Mounting/fixing:

|                                   |     |                             |
|-----------------------------------|-----|-----------------------------|
| Dimension de la tête de tournevis |     | Standard screwdriver Size 1 |
| Tightening torque                 |     |                             |
| • with screw-type terminals       | N·m | 0.4 ... 0.7                 |

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

##### Cax online generator:

<http://www.siemens.com/cax>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RK1903-1AB00/all>



last change:

Mar 5, 2013