



TM-PF 30 S47-C1 FOR ET 200S PM-D F 3/4 TERMINAL
MODULE FOR POTENTIAL GROUP,
WITH SUPPLY U 1/2 AND SENSOR CONNECTION

General technical data:

Product designation		Terminal module
Product-type designation		TM-PF30 S47-C1 for PM-D F3,4
Design of the product		for potential group, infeed U1, U2 with end cover
Mounting height	mm	196.5
Installation width	mm	30
Mounting depth	mm	102
Protection class IP		IP20
Insulation voltage / rated value	V	500
Operating voltage • for DC / rated value	V	24
Operating current / rated value	A	10
Type of the connectable conductor cross-sections • solid • finely stranded / with wire end processing • for AWG conductors • solid • stranded		1x (0.14 ... 2.5 mm ²) 1x (0.14 ... 1.5 mm ²), acc. to IEC 60947 1x (18 ... 22) 1x (18 ... 22)

Mounting/fixing:

Dimension de la tête de tournevis	Standard screwdriver Size 1
--	-----------------------------

Tightening torque

- with screw-type terminals

N·m

0.4 ... 0.7

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RK1903-1AC00/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3RK1903-1AC00

last change:

Mar 5, 2013