

TM-PFX30 S47-G1 FOR POTENTIAL GROUP,
WITHOUT SUPPLY FROM LEFT FOR START OF 1 NEW
GROUP 30MM

General technical data:

Product designation		Terminal module
Product-type designation		TM-PFX30 S47-G1 for PM-D F X1
Design of the product		for PMD-F X1 modules without infeed from left
Mounting height	mm	196.5
Installation width	mm	30
Mounting depth	mm	102
Protection class IP		IP20
Insulation voltage / rated value	V	500
Operating voltage		
• for DC / rated value	V	24
Operating current / rated value	A	10
Type of the connectable conductor cross-sections		
• solid		1x (0.14 ... 2.5 mm ²)
• finely stranded / with wire end processing		1x (0.14 ... 1.5 mm ²), acc. to IEC 60947
• for AWG conductors		
• solid		1x (18 ... 22)
• stranded		1x (18 ... 22)

Mounting/fixing:

Dimension de la tête de tournevis		Standard screwdriver Size 1
Tightening torque		
• with screw-type terminals	N·m	0.4 ... 0.7

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3RK1903-3AE00/all>

last change:

Mar 5, 2013