

TM-PFX30 S47-G0 FOR POTENTIAL GROUP,
WITH SUPPLY FROM LEFT FOR ROUTING U1 M SG1 TO
6 FOR EXTERNAL ET200S-STATION 30MM

General technical data:

Product designation		Terminal module
Product-type designation		TM-PFX30 S47-G0 for PM-D F X1
Design of the product		for PMD-F X1 modules with infeed from left
Mounting height	mm	196.5
Installation width	mm	30
Mounting depth	mm	102
Protection class IP		IP20
Insulation voltage / rated value	V	500
Operating voltage • for DC / rated value	V	24
Operating current / rated value	A	10
Type of the connectable conductor cross-sections • solid • finely stranded / with wire end processing • for AWG conductors • solid • stranded		1x (0.14 ... 2.5 mm ²) 1x (0.14 ... 1.5 mm ²), acc. to IEC 60947 1x (18 ... 22) 1x (18 ... 22)

Mounting/fixing:

Dimension de la tête de tournevis		Standard screwdriver Size 1
Tightening torque • with screw-type terminals	N·m	0.4 ... 0.7

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)
<http://www.siemens.com/industrial-controls/mall>

Cax online generator:
<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<http://support.automation.siemens.com/WWW/view/en/3RK1903-3AE10/all>

last change:

Mar 5, 2013