



Figure similar

ET 200SP MS starter kit including 3RK 1308 motor starter 0.9 - 3 A, reversing starter, BaseUnit with infeed 24 V and 500 V, EMC distance module (blank module 15 mm)

product brand name	SIMATIC
product category	Motor starter
product designation	Starter kit
product type designation	ET 200SP
General technical data	
equipment version according to IEC 60947-4-2	3
product function	Reversing starter
on-site operation	Yes
intrinsic device protection	Yes
remote firmware update	Yes
for power supply reverse polarity protection	Yes
insulation voltage rated value	500 V
degree of pollution	2
overvoltage category	III
surge voltage resistance rated value	6 kV
maximum permissible voltage for protective separation	
between main and auxiliary circuit	500 V
shock resistance	6g / 11 ms
vibration resistance	15 mm to 6 Hz; 2g to 500 Hz
mechanical service life (operating cycles) of the main contacts typical	30 000 000
type of assignment	1
utilization category	
according to IEC 60947-4-2	AC-53a: 3 A: (8-0,7: 70-32)
reference code according to IEC 81346-2	Q
Substance Prohibittance (Date)	03/13/2019
Weight	0.81 kg
product function	
direct start	Yes
reverse starting	Yes
product component motor brake output	No
product function short circuit protection	Yes
design of short-circuit protection	fuse
maximum short-circuit current breaking capacity (Icu)	
at 400 V rated value	55 kA
at 500 V rated value	55 kA
at 500 V according to UL 60947 rated value	100 kA
Electromagnetic compatibility	
EMC emitted interference according to IEC 60947-1	class A

EMC immunity according to IEC 60947-1	Class A
conducted interference	
• due to burst according to IEC 61000-4-4	2 kV
• due to conductor-earth surge according to IEC 61000-4-5	2 kV
• due to conductor-conductor surge according to IEC 61000-4-5	1 kV
• due to high-frequency radiation according to IEC 61000-4-6	Class A
field-based interference according to IEC 61000-4-3	10 V/m
electrostatic discharge according to IEC 61000-4-2	8 kV air discharge
conducted HF interference emissions according to CISPR11	Class A for industrial environment
field-bound HF interference emission according to CISPR11	Class A for industrial environment
Safety related data	
safe state	Load circuit open
Electrical Safety	
touch protection against electrical shock	finger-safe
protection class IP on the front according to IEC 60529	IP20
touch protection on the front according to IEC 60529	finger-safe
Main circuit	
number of poles for main current circuit	3
design of the switching contact	Hybrid
adjustable current response value current of the current-dependent overload release	0.9 ... 3 A
minimum load [%]	20 %
type of the motor protection	solid-state
operating voltage rated value	48 ... 500 V
operating frequency 1 rated value	50 Hz
operating frequency 2 rated value	60 Hz
relative symmetrical tolerance of the operating frequency	5 %
relative positive tolerance of the operating frequency	5 %
relative negative tolerance of the operating frequency	5 %
operational current at AC at 400 V rated value	3 A
operating power for 3-phase motors at 400 V at 50 Hz	0.37 ... 1.1 kW
Inputs/ Outputs	
number of digital inputs	4
Supply voltage	
type of voltage of the supply voltage	DC
supply voltage 1 at DC rated value	
• minimum permissible	20.4 V
• maximum permissible	28.8 V
supply voltage at DC rated value	24 V
duration of inrush current peak at 24 V	0.14 ms
Response times	
OFF-delay time	35 ... 50 ms
Installation/ mounting/ dimensions	
mounting position	Vertical, horizontal (observe derating)
fastening method	pluggable in BaseUnit
height	142 mm
width	30 mm
depth	150 mm
required spacing with side-by-side mounting	
• upwards	50 mm
• downwards	50 mm
Ambient conditions	
installation altitude at height above sea level maximum	4 000 m; For derating see manual
ambient temperature	
• during operation	-25 ... +60 °C; For derating see manual
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
environmental category during operation according to IEC 60721	3K6 (no formation of ice, no condensation), 3C3 (no salt mist), 3S2 (sand must not get into the devices)

relative humidity during operation	10 ... 95 %				
air pressure according to SN 31205	900 ... 1 060 hPa				
Communication/ Protocol					
protocol is supported					
• PROFIBUS DP protocol	Yes				
• PROFINET protocol	Yes				
product function bus communication	Yes				
protocol is supported AS-Interface protocol	No				
product function					
• supports PROFinergy measured values	Yes				
• supports PROFinergy shutdown	Yes				
type of electrical connection of the communication interface	Plug contact to Base Unit				
Connections/ Terminals					
type of electrical connection					
• 1 for digital input signals	Pluggable module - accessory				
type of electrical connection					
• for main energy infeed	Plug contact to Base Unit				
• for load-side outgoing feeder	Plug contact to Base Unit				
• for supply voltage line-side	Plug contact to Base Unit				
wire length for motor unshielded maximum	200 m				
UL/CSA ratings					
full-load current (FLA) for 3-phase AC motor at 480 V rated value	3 A				
current with locked rotor (LRA) for 3-phase AC motor at 480 V rated value	24 A				
yielded mechanical performance [hp]					
• for single-phase AC motor					
— at 230 V rated value	0.25 hp				
• for 3-phase AC motor					
— at 200/208 V rated value	0.5 hp				
— at 220/230 V rated value	0.5 hp				
— at 460/480 V rated value	1.5 hp				
operating voltage at AC at 60 Hz according to CSA and UL rated value	480 V				
Approvals Certificates					
General Product Approval	Test Certificates	other	Environment		
			Type Test Certificates/Test Report	Confirmation	Environmental Confirmations
Further information					
Information on the packaging					
https://support.industry.siemens.com/cs/ww/en/view/109813875					
Information- and Downloadcenter (Catalogs, Brochures,...)					
https://www.siemens.com/ic10					
Industry Mall (Online ordering system)					
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1908-1SK00					
Cax online generator					
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1908-1SK00					
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)					
https://support.industry.siemens.com/cs/ww/en/ps/3RK1908-1SK00					
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)					
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1908-1SK00&lang=en					

last modified:

4/2/2025 